

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com



Follow Us Twitter







Noiseblocker NB-eLoop B12-2 120mm x 25mm Ultra Silent Bionic Blade Fan - 1300 RPM - 16.7 dBA

\$19.95

Product Images





Short Description

The world's first high-tech compact fan with patented bionic Bionic rotor loop is from Germany. Developed with the support of the Federal Economics Ministry and the bionic Dr. Rudolf Bannasch we make with the NB-ELOOP series against the currently most advanced fan in the world. The NB-ELOOP series sets new records in almost every category and convinced by our quality product. Newly developed storage and drive as well as the tried-NB cable management and a 12-piece mounting for vibration-free mounting complement the

Description

The world's first high-tech compact fan with patented bionic Bionic rotor loop is from Germany. Developed with the support of the Federal Economics Ministry and the bionic Dr. Rudolf Bannasch we make with the NB-ELOOP series against the currently most advanced fan in the world. The NB-ELOOP series sets new records in almost every category and convinced by our quality product. Newly developed storage and drive as well as the tried-NB cable management and a 12-piece mounting for vibration-free mounting complement the overall unique setup.

The new design eliminates the edge of the vertebrae are formed between the suction and pressure side of the wing tips. The tip vortices are here broken down into smaller vortex edge and spread evenly. The resulting at the blade trailing edge tip vortex can be reduced by vorticity guides to a minimum. The result is a significant improvement in glide ratio which leads to a reduction of the aerodynamic flow induced noise and improves energy efficiency. dust-resistant super-smooth surface, original material Bayer Makrolon ®.

Features

Bionic Fan Chassis

- Aerodynamically optimized Abströmfeld
- 4 resonance / interference absorbers (Deep Sound Design)
- Magnified by Einströmfeld ply construction
- Super-linear performance throughout the rev range, flow-optimized
- Glass fiber reinforced PBT frame Materialmassierter UL94V0 30% GF

NB-FKA 2 Drive

- Auto restart function for safe start.
- Built-in locking and overload protection.
- NB scalable Wide Range Electronics
- Low starting voltage
- Speed signal line
- AntiDust Technology (completely dust-Protected Motor)

NB-2 magnetic levitation bearing NanoSLI

- · Lubrication and noise reduction of vertical and horizontal operation without increasing the volume
- AntiDust Technology (completely dust-proof bearings)
- Lubrication with special nanotechnology for high durability and low operating noise

NB Cable Management

• Plug-sheathed cable, 1x 20cm + 1 x 50cm

Vibration-free mounting

• The included 12-piece mounting kit allows for vibration-free assembly, which reduces the operating noise when installed.

Warranty

• Six years, according to NB warranty terms

Specifications

Dimensions:	120 x 120 x 25 mm
Speed:	1300 RPM ±10%
Noise:	16.7
Max. Airflow:	51.1 CFM 86.9 m^3/h
Static Pressure:	1.042 mmH2O
Bearing:	NB-2 magnetic levitation bearing NanoSLI®
Voltage Range:	3.4 - 12.0 V DC
Starting Voltage:	3.4 V DC
Input Current:	0.07A
Input Power:	0.85W
MTBF at 25°C:	160,000 hrs.
Operating Temp.:	-10°C to +60°C
Chassis Material:	PBT 30%GF
Impeller Material:	Bayer Makrolon (PC)
Vibration Dampening Material:	Silicone Mix
Weight:	123g
Warranty:	6 Years

4/19/24

Additional Information

Brand	Blacknoise
SKU	NB-ELOOP-B12-2
Weight	0.5000
Color	Black
Fan Dimensions	120mm
Fan Width	25mm
Fan Connection	3-Pin
Fan Voltage	12 VDC
Fan RPM	1300
Fan CFM	51
Fan Noise (dB)	17
Vendor SKU/EAN	4250051906424



4