


Performance-PCs.com

1701 R. J. Conlan Blvd. NE. Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222



Like Us Facebook Follow Us Twitter





www.performance-pcs.com sales@performance-pcs.com

Phobya SLI Connector Plexi - Slot 3



Product Images



Short Description

The variable SLI connection piece connects two VGA waterblocks which are operated in a system in SLI mode . The special of this piece is that it approximately 12mm in length is adjustable . Therefore, this connector can be used with graphics cards from different manufacturers.

Description

The variable SLI connection piece connects two VGA waterblocks which are operated in a system in SLI mode . The special of this piece is that it approximately 12mm in length is adjustable . Therefore, this connector can be used with graphics cards from different manufacturers. The nipple can be used to either turn the graphics cards in a row, or if you put 2 nipples between 2 graphics cards, both coolers can be durchströhmt parallel. This is of course also possible with 3 graphics card coolers. The connector pieces are available in 3 lengths:

Article 94248 for 1 slot Article 94249 for 2 slot Article 94250 for 3 slot motherboards.

Specifications

- A direct connector between 2 graphics cards .
- Thread: G1 / 4 inch Material : Brass nickel plated
- Distance between the radiators : 59.5 to 70.9 mm
- Suitable for motherboards with 1 slot spacing between the two graphics cards.
- Suitable for crossfire graphics card cooler of such Koolance , XSPC , Alphacool

Warning:

The nipple is compatible only with video cards that each have 2 1/4 inch thread top and bottom. In the coolers only have connectors on one side (eg, Aqua computer) can not be mounted to the nipple .

Scope of delivery: SLI connector (without fittings)

Note: At this connector nipples are additionally required.

Additional Information

Brand	Phobya
SKU	PH-94250
Weight	0.1000
Color	Clear
Vga	Universal
Block GPU Type	Nvidia/AMD
Block Accessory Type	Rigid Tube

