

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA


Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com



Follow Us Twitter







# Vandal Resistant Latching Switch 22/19mm - Black

\$10.95

# **Product Images**















## **Short Description**

The vandal resistant Latching on/off switch is the ideal switch for computer modding enthusiasts. A momentary switch is typically used for a PC's power and reset button. When turned on, the ring or dot around the push button illuminates in the specified color. Easy to install and will fit it many case switch holes, on a regular 3.5 or 5.25 inch bay cover, or wherever you chose to mount it.

### Description

The vandal resistant Latching on/off switch is the ideal switch for computer modding enthusiasts. A latching switch is typically used for turning on and off computer case accessories. When turned on, the ring or dot around the push button illuminates in the specified color. Easy to install and will fit it many case switch holes, on a regular 3.5 or 5.25 inch bay cover, or wherever you chose to mount it.

Manufactured from aluminum, this extensive range of vandal resistant security switches are designed for use in potentially hostile environments, such as access control applications, auto, truck, outdoor, marine use, or, in the case of PC modders, powering up your computers fans, lighting and other things from off to on.

This is a bare switch only and will need wiring to be able to use. Optional cable harness' can be ordered along with the switch. Wiring instructions are included.

#### **Features**

- Front Panel Mounting
- No LED Illumination
- 22mm bezel diameter
- 19mm shaft (install) diameter
- S.P. Push to Make
- 50mA, 24V dc contact rating Switch
- Separate LED Terminals

# **Specifications**

- Terminations: (2.8mm tabs)
- Switching: S.P. Push to make, tactile S.P.or Push/Latch
- Max. Rating: 50mA, 24V d.c. switch
- Contact Resistance: <100m $\Omega$ .
- Insulation Resistance: >103 M $\Omega$ .
- Dielectric Strength: Contact to Panel >2.0kV
- Contact to Contact 1500V Contact
- Operating Temp. Range: .30C to +70C
- Sealing (Front of panel only): Protection Classification: IP66 EN60529
- Materials:

Switch assembly: V-0 rated Polyamide (Nylon)

Tags: Copper Alloy Terminals: Copper Alloy

Switch Body & Button: Aluminum O rings: Nitrile and Silicone Contact Plate: Gold Plated

#### **Additional Information**

Brand	Mod/Smart
SKU	VSW22-LAT-BK
Weight	0.1500
Color	Black
Switch Type	Vandal (Latching)
Material	Aluminum

3 5/6/24

