



EK-HFB High Flow Barb Fitting 12mm - Red

Special Price
\$3.50 was
\$3.99

Product Images



Short Description

EK-HFB Fitting (High Flow Barb) is a soft-tube barb fitting, designed for use with flexible soft tubing such as PVC, EPDM, Norprene, silicone or any other type of compatible flexible tube.

Description

EK-HFB Fitting (*High Flow Barb*) is a soft-tube barb fitting, designed for use with flexible soft tubing such as PVC, EPDM, Norprene, silicone or any other type of compatible flexible tube.



EK-HFB Fitting is a stylish looking variant of the classic high flow barb fitting and requires the use of hose clamps or similiar substitute for safest operation.

The barb is made from nickel-plated CNC machined brass with quality O-rings while the ring is made from CNC machined aluminium. These fittings are fully compatible with EK-AF series (45°/90°) angled adapters.

These fittings can be either tightened by hand or by using [Allen Key 9mm](#) (not included, available for separate purchase).

Specifications

Technical data:

- Thread: G1/4" BSP; 4.5mm male thread lenght
- Supported tube: 12mm (ID; roughly equals 1/2" ID)
- Outer diameter of the tube: unlimited
- Outer diameter of a fitting: 19.8mm
- Installed height: 19mm
- Compatible tubing: PVC, EPDM, Norprene, silicone, most types of flexible tube

ROHS 2.0 Compliant!

Made in Slovenia - Europe!

PLEASE NOTE:

- This fitting is to be used only with correctly sized tubing!
- Do not use excessive force when attaching fitting barbs using Allen Key 9mm in order to prevent water block damage!
- Use appropriate hose clamp or substitute to secure tubing to the barb!

Additional Information

Brand	EK Waterblocks
SKU	EK-HFB-12-RD-D
Weight	0.1500
Special Order	No
Fitting Type	Barb
Fitting Size	7/16"
Fitting Angle	Straight
Vendor SKU/EAN	3831109846834
Special Price	\$3.50

