




Noctua NF-A9 FLX Quiet Computer Fan 92mm

\$20.95

Product Images





Short Description

The NF-A9 is a highly optimised, premium quality quiet 92mm fan. Featuring Noctua's AAO (Advanced Acoustic Optimisation) frame as well as sophisticated aerodynamic design measures such as Flow Acceleration Channels, the NF-A9 further improves the renowned quiet cooling performance of the award-winning NF-B9.

Description

The NF-A9 is a highly optimised, premium quality quiet 92mm fan. Featuring Noctua's AAO (Advanced Acoustic Optimisation) frame as well as sophisticated aerodynamic design measures such as Flow Acceleration Channels, the NF-A9 further improves the renowned quiet cooling performance of the award-winning NF-B9. The FLX version provides 1600/1250/1050rpm speed settings via the supplied Low-Noise Adaptors in order to provide full flexibility in fine-tuning the fan for maximum ventilation performance or near-silent operation. Its superb running smoothness, reference-class SSO2 bearing and Noctua's trusted premium quality make it an elite choice for the highest demands.

Features



Succeeding the award-winning NF-R9 Noctua's NF-B9 fan has become a default-choice among PC enthusiasts looking for a premium quality quiet 92mm fan. Thanks to its thoroughgoing aerodynamic optimisations, the NF-A9 provides higher static pressure and an even better airflow/noise ratio than its much acclaimed predecessor.



Flow Acceleration Channels

The NF-A9 impeller features suction side Flow Acceleration Channels. By speeding up the airflow at the crucial outer blade regions, this measure reduces suction side flow separation and thus leads to better efficiency and lower vortex noise.



AAO Frame

Noctua's AAO (Advanced Acoustic Optimization) frames feature integrated anti-vibration pads as well as Noctua's proprietary Stepped Inlet Design and Inner Surface Microstructures, both of which further refine the fan's performance/noise efficiency.



Stepped Inlet Design

Noctua's Stepped Inlet Design adds turbulence to the influx in order to facilitate the transition from laminar flow to turbulent flow, which reduces tonal intake noise, improves flow attachment and increases suction capacity, especially in space restricted environments.



Inner Surface Microstructures

With the tips of the fan blades ploughing through the boundary layer created by the Inner Surface Microstructures, flow separation from the suction side of the blades is significantly suppressed, which results in reduced blade passing noise and improved airflow and pressure efficiency.




Noctua Integrated Anti-Vibration Pads

Integrated Anti-Vibration Pads made from extra-soft silicone minimise the transmission of minute vibrations while maintaining full compatibility with all standard screws and other mounting systems.



SSO2 Bearing

The NF-A9 features the further optimized second generation of Noctua's renowned, time-tested SSO bearing. With SSO2, the rear magnet is placed closer to the axis to provide even better stabilization, precision and durability.




Smooth Commutation Drive 2

The latest version of Noctua's advanced Smooth Commutation Drive system ensures superb running smoothness by eliminating torque variations and switching noises. This makes the NF-A9 remarkably quiet even at very close distance.



3 speed settings for full flexibility

Providing 1600, 1250 and 1050 rpm speed settings via the supplied Low-Noise and Ultra-Low-Noise Adapters, the NF-A9 FLX (Flexibility) can be fine-tuned for superior airflow or maximum quietness.



Extensive Cabling Options

The fan's short 20cm primary cable minimises cable clutter in typical applications while the supplied 30cm extension provides extended reach when necessary. Both cables are fully sleeved and a 4-pin y-cable allows to connect a second NF-A8 fan to the same PWM fan header for automatic control.



6 years Manufacturer's Warranty

Noctua fans are renowned for their impeccable quality and outstanding longevity. Like all Noctua fans, the NF-A9 features an MTBF rating of more than 150.000 hours and comes with a full 6 years manufacturer's warranty.

Specifications

Size	92x92x25 mm
Connector	3-pin
Bearing	SSO2
Blade Geometry	A-Series with Flow Acceleration Channels
Frame Technology	AAO (Advanced Acoustic Optimization)
Rotational Speed (+/- 10%)	1600 RPM
Rotational Speed with L.N.A. (+/- 10%)	1250 RPM
Rotational Speed with U.L.N.A. (+/- 10%)	1250 RPM
Airflow	64.6 m ³ h - 38.02 cfm
Airflow with L.N.A.	51.1 m ³ h - 30.07 cfm
Airflow with U.L.N.A.	42.9 m ³ h - 25.25 cfm
Acoustical Noise	22.8 dB(A)
Acoustical Noise with L.N.A.	11.6 dB(A)
Acoustical Noise with U.L.N.A.	8.4 dB(A)
Static Pressure	1.62 mm H ₂ O
Static Pressure with L.N.A.	1.04mm H ₂ O
Static Pressure with U.L.N.A.	0.71mm H ₂ O
Max. Input Power	0.84 W
Input Current	0.07 A
Voltage Range	12V
MTBF	> 150,000 h
Scope of Delivery	<ul style="list-style-type: none"> • Low-Noise Adapter (L.N.A.) • 3:4-Pin Adapter • 30cm Extension Cable • 4 Vibration Compensators • 4 Fan Screws
Warranty	6 years

Additional Information

Brand	Noctua
SKU	NFA9FLX
Weight	1.2000
Color	Brown
Fan Dimensions	92mm
Fan Width	25mm
Fan Connection	3-Pin
Fan Voltage	12 VDC
Fan RPM	1600
Fan CFM	38
Fan Noise (dB)	23

