

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com



Follow Us Twitter









\$114.95

Product Images





Short Description

Koolance 702 series coolant is used by many industries requiring a high performance, low-toxicity, reliable coolant with corrosion inhibitors. A high quality coolant is extremely important for addressing dissimilar metals long-term. Koolance liquids will not clog components and can typically be used for 2-3 years before replacement is recommended.

Description

Koolance 702 series coolant is used by many industries requiring a high performance, low-toxicity, reliable coolant with corrosion inhibitors. A high quality coolant is extremely important for addressing dissimilar metals long-term. Koolance liquids will not clog components and can typically be used for 2-3 years before replacement is recommended.

This container includes 5 liters (169 fl oz) of prediluted coolant. It's recommended to replace the coolant at least every 2-3 years, or immediately if there is any change in color or clarity.

Features

The freezing point is -15°C (5°F). This coolant has been tested with the following materials:

- Metals: copper, aluminum, brass, lead, stainless steel, steel, nickel, gold
- Plastics: PE, PP, PVC, POM, PMMA, PPO, PA66, PPS, PPE, PEI, PES, PBT, PETG
- Rubber: EPDM

NOTE: Not recommended for polycarbonate plastics or other PC-based plastics.

Specifications

0

Additional Information

Brand	Koolance
SKU	LIQ-702BU-05L
Weight	14.2500
Color	UV Blue
Fluid Type	DI Water Based
Volume	5 liter



3 4/18/24