

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com











PrimoChill 1/2in. Rigid Fitting to Flex Tubing Insert - 6 Pack

\$6.95

Product Images

















Short Description

PrimoChill's RSX compression fittings has made color adaptation in your system seemless. Expanding on that we brainstormed up these inserts to allow you to use flexible tubing with Rigid fittings. This concept allows you to switch between flexible and rigid in your system without buying new fittings.

Description

PrimoChill's RSX compression fittings has made color adaptation in your system seemless. Expanding on that we brainstormed up these inserts to allow you to use flexible tubing with Rigid fittings. This concept allows you to switch between flexible and rigid in your system without buying new fittings. Take it one step further and use mix matched tubing in the same system while all fittings look the same! These inserts are compatible with RSX, Revolver and Ghost compressions and couplers.

The RSX fitting truly represents the principles of PrimoChill. A fitting built for functionality complimented by

its distinct aesthetics. Now they are available for all applications.

Features

UNIQUE DESIGN

Tube Insert expands on our Patent Pending compression fittings that lead the industry in innovation and ease of use.

CONTINUED INNOVATION

A continuous industry leader in style and function within the water cooling community.

SIMPLIFIED USAGE

Quick and simple installation with minimization of leakage

Specifications

Specifications:

- Material:Nickel Plated Brass
- Height:10mm total

Compatibility:

- Tube Compatibility:PrimoFlex Advanced LRT Flexible Tubing 3/8in. ID x 1/2in. OD
- Fitting Compatibility:RSX, Revolver and Ghost compressions and couplers.

Included Parts:

• 6x PrimoChill 1/2in. Rigid Fitting to Flex Tubing Insert

Installation:

- Cut flexible tubing end square
- Push insert into tube end till flush
- Follow same installation as rigid tube usage
- Install thread o-ring snug to base
- Install tube o-ring on outside of tube, inside of the compression cap
- No installation tool required for cap. Finger tighten only.
- The Revolver tool was designed for removing the cap only, not installing them.
- RSX caps are coated with a durable powder coat but we still recommend handling with care so you can
 enjoy the finish for years to come.

Note: Make sure to follow external o-ring installation as normal once insert is installed. The insert gives the flexible tubing some rigidity to allow you to install it as if it was PETG.

Additional Information

Brand	Primochill
SKU	RF-RSX3812-6
Weight	0.6000
Special Order	No
Fitting Type	Adapter
Fitting Size	3/8" x 1/2"
Fitting Angle	Straight
Fitting Finish	Chrome



4