




# Thermaltake Smart 700W ATX12V & EPS12V Power Supply

Special Price  
**\$62.99** was  
**\$69.99**

## Product Images





## Short Description

---

Incorporating various high-quality components, the Smart Series – models are rated from 500W to 700W – saves energy through its high efficiency of up to 86% and accommodates any mainstream build with the most demanding requirements. An embedded intelligent cooling fan delivers excellent airflow at an exceptionally low noise level. Additionally, the Single +12V rail design enables non-stop usage with stable and reliable performance.

## Description

---

Incorporating various high-quality components, the Smart Series – models are rated from 500W to 700W – saves energy through its high efficiency of up to 86% and accommodates any mainstream build with the most demanding requirements. An embedded intelligent cooling fan delivers excellent airflow at an exceptionally low noise level. Additionally, the Single +12V rail design enables non-stop usage with stable and reliable performance.





## Features

### 120mm Ultra Quiet Fan

Smart Series adopt 120mm cooling fan delivers excellent airflow at an exceptionally low noise level.

### Multiple Connectors

Smart 700W connector's specification as below:

						
MODEL / CABLE	Main Power Connector (20+4Pin)	ATX 12V (4+4Pin)	Peripheral (4Pin)	SATA (5Pin)	PCI-E (6+2Pin)	Floppy (4Pin)
SMART 700W	1	1	5	6	2	1

### 80 PLUS Standard Certified and Haswell Ready

Smart Series saves energy through its high energy efficiency of up to 86% and is 80 PLUS® Standard Certified.

### High-Quality Components

High quality components enable non-stop usage with stable and reliable performance, no more capacitor explosion and leakage.

### Single +12V Output

Smart Series is equipped with a powerful +12V rail, superior performance under all types of system loading.

## Specifications

P/N	PS-SPD-0700NPCW**-W
Short P/N	SPD-0700P
Model	SP-700AH2NKW
Type	Intel ATX 12V 2.3
Max. Output Capacity	700W

Color	Black
Dimension (H x W x D)	86mm x 150mm x 140mm
PFC (Power Factor Correction)	Active PFC
Power Good Signal	100-500 msec
Hold Up Time	16msec (minimum) within 60% load
Input current	12A max
Input Frequency Range	50 Hz - 60 Hz
Input Voltage	100Vac - 240Vac
Operating Temperature	5°C to +40°C
Operating Humidity	20% to 85%,non-condensing
Operating Temperature	-40 °C to +55 °C
Operating Humidity	10% to 95%, non-condensing
Cooling System	120mm Fan: 1800 R.P.M. ± 10%
Efficiency	80-87% efficiency @ 20-100% load
MTBF	100,000 hrs minimum
Safety Approval	CE/CB/TUV/ UL/ FCC
PCI-E Connector	PCI-E 6+2pin x 2

\* Specifications are subject to change without notice.

\* The product picture(s) is only for your reference, it may differ from the actual product.

## Additional Information

Brand	Thermaltake
SKU	PS-SPD-0700NPCWUS-W
Weight	6.0000
Color	Black
PSU Type	ATX
PSU Style	Non-Modular
PSU Wattage	700W
PSU Efficiency	80 PLUS
Special Price	\$62.99

