

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com













# Toughpower Grand RGB 850W Platinum

\$159.99

## **Product Images**













### **Short Description**

Thermaltake, as the pioneer who incorporates RGB lights into PSU, introduces the Thermaltake Toughpower Grand RGB Series, coming with a pre-installed, patented 256 colors Riing 14 RGB fan with 5 lighting modes (RGB Cycle Mode, Solid Red, Solid Green, Solid Blue, and Solid White), LEDs Off and a built-in memory function.

Featuring capacities ranging from 850W to 1200W and 80 PLUS Platinum certification, Toughpower Grand RGB Series adopts the highest quality components and fully modular design that always accommodate any mainstream build under any circumstances.

## Description

Thermaltake, as the pioneer who incorporates RGB lights into PSU, introduces the Thermaltake Toughpower Grand RGB Series, coming with a pre-installed, patented 256 colors Riing 14 RGB fan with 5 lighting modes (RGB Cycle Mode, Solid Red, Solid Green, Solid Blue, and Solid White), LEDs Off and a built-in memory function.

Featuring capacities ranging from 850W to 1200W and 80 PLUS Platinum certification, Toughpower Grand RGB Series adopts the highest quality components and fully modular design that always accommodate any mainstream build under any circumstances.

#### **Features**

#### One Button to Your Desired Color

By pressing the RGB lighting button, the fan color can be switched among a 256 Color RGB Cycle with variants including Solid Red, Green, Blue, White, and a LED Off mode. The fan is also constructed with a built-in memory function, saving the color applied and insuring the same color selection every time you boot your PC.

#### Compact Design for Easy Installation

With its short depth of 160mm, Toughpower Grand RGB 850W Platinum gives high compatibility to allow users more room for cable routing, cooling and more.

New Platform for Better Ripple Noise Performance and Steady Voltage Output

All new circuit design with PFC & LLC digital controllers efficiently reduces ripple noise and gives steady voltage output.

Power Supply Fan Face-Up Placement for Better Cooling

With the face-up placement of the fan, users can freely gaze upon their patented circular 256 multi-colored RGB fan and at the same time obtaining additional performance by using the fan as a additional exhaust mechanism, repelling unwanted heat from your chassis. As the thermal image testing shown, the temperature of PSU and computer system will decrease around 3°C (5.4 °F) by placing PSU face-up.

\* All images are for reference only; actual specification and lighting effects are based on the real product.

#### Riing 14 RGB Fan with Concentrated Compression Fan Blade

Riing 14 RGB fan blade is designed for high static pressure requirements of demanding applications; the concentrated compression blade is engineered to focus the weaker, inner circle of air outward, allowing the outer section to pressurize the air. The fan blades are optimized to enhance static pressure for an impressive cooling performance. Hydraulic bearings for silent operation guarantee ultra-low noise, and the anti-vibration mounting system strengthens the product's stability during operation. Moreover, In-mold injection anti-vibration rubber pads provide hassle-free usage for 80% protection coverage, including all four corners.

#### Ultra Quiet Smart Zero Fan

Smart Zero Fan ensures zero noise when the fan operates below 40% working load to minimize audible noise. The fan will operate when the power supply working load over 40%. A switch is provided for those who prefer the fan to spin constantly.

#### < 30 mV Low Ripple Noise

All ripples are lower than 30mV for high stability on +12V, +5V, or +3.3V from 0% to 100% load to ensure a high quality power supply. Low ripple noise will keep your performance-critical components, such as highend graphics cards, to operate reliably for longer.

Extremely Strict Voltage Regulation < ±2%

The voltage regulation of the PSU is set to no more than  $\pm 2\%$  for major rails to meet the highest performance. The strict voltage regulation of the Toughpower Grand RGB Platinum is better than Intel's standard  $\pm 5\%$  for major rails and  $\pm 10\%$  for -12V.

100% High Quality Japanese 105°C/221°F Capacitors

100% high quality 105 °C (221 ° F) Japanese made capacitors which greatly improve the durability and offer the highest stability and reliability.

High Amperage Single +12V Rail & DC to DC Design

Toughpower Grand RGB 850 Platinum is equipped with a powerful single +12V rail, eliminating the limitations caused by voltage distributions, delivering the power your CPU and VGA demand in any situations. Besides, with DC to DC design, the unit optimizes maximum energy harvest for computer systems, providing the best compatibility, conversion efficiency and stable voltage output.

Fully Modular Low-Profile Flat Cable

Fully modular Toughpower Grand RGB 850W Platinum offers cable selection for users while powering the system at an advantageous voltage. Low-profile flat black cable can make cable management easier, reduce clutter and increase airflow inside the chassis.

80 PLUS Platinum Certified and Intel C6/C7 States Ready

Deliver up to 92% efficiency under real world load conditions to promise lowest power losses. Additionally, Toughpower Grand RGB Platinum Series has been optimized to work with all generations of Intel's processors to achieve maximum energy saving.

RGB Lighting Provides Best Aesthetics for All Chassis

Toughpower Grand RGB Platinum Series is the best idea for users to go with when they are looking for an RGB PSU which permits remarkable functionality and aesthetics in all cases, especially Open Frame or Tower cases.

## **Specifications**

P/N	PS-TPG-0850F1FAPx-1
Short P/N	TPG-0850F1FAP
PSU Model	TPG-850AH3FCP
PSU Type	ATX 12V v2.4 and EPS v2.92
Max. Output Capacity	850W

Peak Output Capacity	1020W	
Color	Black	
Dimension ( W/H /D )	150mm(W) x 86mm(H) x 160mm(D)	
PFC (Power Factor Correction)	Active PFC	
Power Good Signal	100-500 msec	
Hold Up Time	> 16msec at 100% of full load	
Input Current	12A	
Input Frequency Range	50Hz - 60Hz	
Input Voltage	100V - 240V~	
Operating Temperature	0°C to + 50°C	
Operating Humidity	20% to 90%,non-condensing	
Storage Temperature	-20°C to + 70°C	
Storage Humidity	5% to 95%, non-condensing	
Cooling System	14cm hydraulic bearing fan	
Efficiency	Meet 80 PLUS®Platinum at 115Vac input.	
MTBF	120,000 hrs minimum	
Safety Approval	CE/cTUVus/TÜV /FCC/CCC/EAC /S-Mark	
PCI-E 6+2pin	6	
Protection	OVP, SCP, OPP, UVP, OTP,OCP	

<sup>\*</sup> Specifications are subject to change without notice.

\* The product picture(s) is only for your reference, it may differ from the actual product.

# Additional Information

Brand	Thermaltake
SKU	PS-TPG-0850F1FAPU-1
Weight	10.0000
Color	Black
PSU Type	ATX
PSU Style	Modular
PSU Wattage	850W
PSU Efficiency	80 PLUS Platinum



4/20/24