



Aquacomputer aqualis PRO 880 ml with lighting option, G1/4

\$89.75

Product Images



Short Description

The reservoirs of the aqualis series feature a tube made from borosilicate glass, featuring, unlike the

common Plexi reservoirs, very high hardness and scratch resistance paired with low thermal expansion and excellent chemical and thermal resistance.

Description

The reservoirs of the aqualis series feature a tube made from borosilicate glass, featuring, unlike the common Plexi reservoirs, very high hardness and scratch resistance paired with low thermal expansion and excellent chemical and thermal resistance.

An outer diameter of 75mm and a wall thickness of 5mm ensure high capacity and sturdiness of the reservoir. Bottom and top piece of the aqualis series reservoirs is made from Delrin, a nickel plated brass tube connects them. An optical highlight is the integrated water column effect: If the middle thread is used as the inlet, the coolant will flow through the brass tube to the top of the reservoir and exit via the eight openings, resulting in a great effect especially in combination with lighting.

A thin Plexi plate near the bottom of the aqualis effectively reduces the amount of air being sucked back into the cooling loop to a minimum. Alternatively a thread at the side of the reservoir can be used as the inlet, directing the flow of coolant through the bottom of the reservoir. For this configuration a deflection plate is included, ensuring effective de-aeration of the coolant.

The aqualis PRO reservoirs feature an additional Plexi window integrated into the bottom piece, offering space for installation of up to six LEDs (type 5mm). Additionally, the reservoirs are pre-equipped to allow installation of a fill level sensor at a later point in time.

The aqualis XT reservoirs also feature the bottom Plexi window and space for installation of up to 6 LEDs (type 5mm).

A fill level sensor with USB and aquabus interface, a configurable alarm channel and an external temperature sensor input is also included.

For monitoring and configuration the software aquasuite is available for download. A 4-pin aquabus interface allows direct connection to an aquaero 5 (not included). The alarm output can either be configured as an artificial rpm signal for connection to a fan channel with speed monitoring (e.g. Mainboard fan channels) or as a switching channel for e.g. activating a LED in case of an alarm. For alarm monitoring besides the measured flow rate and water temperature, an external temperature sensor input is available. The external temperature sensor input is compatible with all temperature sensors offered by Aqua Computer

All 450ml versions are also available with a Nano coating which lets water drip off of the inner wall of the glass tube.

Specifications

Color:	black
Connector:	G1/4" inner thread
Dimensions:	80 x 80 x 300mm
Fillport:	G1/4" inner thread

LED hole:	Not available
Manufacturer:	Aquacomputer
Material:	borosilicate glass
Model of reservoir:	Aqualis reservoir
Number of connections:	2
Preinstalled pump:	No
Pump compatibility:	For flow pumps
Volume:	880ml

Technical specifications:

- Dimensions without stainless steel mount: approx. 80 x 80 x 300 mm
- Coolant capacity: approx. 880 ml
- Connection thread size: G1/4

Extent of delivery:

- One reservoir
- One stainless steel mount
- One deflection plate made from stainless steel
- Two G1/4" screw plugs (pre-installed)
- Mounting material

Please note: The reservoir is shipped without fittings. Please order suitable fittings separately.

Additional Information

Brand	Aquacomputer
SKU	AQ-34049-D
Weight	3.0000
Color	Clear
Reservoir Type	Tube Res
Tube Res Length	300mm
Vendor SKU/EAN	4260073415521

