

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com





Follow Us Twitter







Alphacool Eiszyklon Aurora RGB - 1100rpm (120x120x25mm)

\$14.50

Product Images























Short Description

The 120 mm Alphacool Eiszyklon RGB fan combines silent operation, high performance and great aesthetics to create a fan suitable for a wide range of users. Due to its high air flow rate and enormous static pressure, the 120 mm Eiszyklon RGB fan is suitable for use on radiators, CPU air coolers and as a case fan. The 120mm Eiszyklon RGB fan has a maximum RPM of 1100rpm, a perfect balance between performance and noise.

Description

The 120 mm Alphacool Eiszyklon RGB fan combines silent operation, high performance and great aesthetics to create a fan suitable for a wide range of users. Due to its high air flow rate and enormous static pressure, the 120 mm Eiszyklon RGB fan is suitable for use on radiators, CPU air coolers and as a case fan. The 120mm Eiszyklon RGB fan has a maximum RPM of 1100rpm, a perfect balance between performance and noise.

Instead of just 4 LEDs in the corners of the fan frame, like you would see with many other fans, Alphacool uses 21 RGB LEDs. These are mounted inside the frame and light up directly on a ring diffuser attached to the end of the fan blades. This produces the laser beam effect. The light is reflected on the shiny black fan blades and are static. This means that no matter how high the speed of the Eiszyklon RGB fan is, the 21 laser beams always remain in the same position. This is far more of an effect on the actual fan blades themselves rather than the defused looking ring around the fan that can be seen on the 120mm Alphacool Eiszyklon RGB LT.

The Alphacool Eismatrix Controller can be used to create many dynamic effects. Static, Breathing, Fading, Marquee, Covering Marquee, Alternating, Spectrum Wave, Pulse and many more effects are possible using this combination. The RGB LEDs can also be dimmed via the controller.

The Eiszyklon fan is connected via a 3-pin fan connector. The Eismatrix Controller is required to control the RGB lighting. Alternatively, you can also use other RGB LED controllers with an appropriate adapter.

Specifications

Manufacturer:	Alphacool
Power input:	1,92 W
Pressure:	1,22 mm H2O
Start voltage:	9,6 V
LED:	RGB
Air flow:	98,54 m³/h
Rated speed:	1100 U/min

Fan bundle:	9x, 4x, 3x
Lifespan (at 25°C):	50.000 h
Size:	120mm
Volume range:	20 - 29,9 dB(A)
Rated speed range:	1000 - 1450 U/min
RPM signal transmission:	Yes
Power connector:	3Pin Molex
Air flow range:	50 - 99 m³/h
Voltage rated:	12V DC
Frame Color:	black
Rotor color:	black
Dimensions:	120 x 120 x 25mm
Volume:	21,0 dB(A)

Technical Details

• Dimensions: 120 x 120 x 25 mm

• Rotational speed: 1100rpm

• LED: 21x RGB

• Anti-vibration corners

• 4Pin RGB connector 60cm

• 3Pin power connector 50cm

• Colour: Mostly black, transparent matt

Scope of Delivery

• 1x Alphacool Eiszyklon Aurora RGB - 1100rpm (120x120x25mm)

Additional Information

phacool
-24803
3000
noke
0mm
mm
Pin
VDC
00
GB .
50197248037
3



5 4/26/24