



# Koolance QD2 Quick Disconnect No-Spill Coupling, Male Panel Barb for 06mm (1/4in)

\$10.49

## Product Images



## Short Description

---

Koolance (patent-pending) quick disconnect no-spill coupling with automatic shutoff. 6mm (1/4in) ID male panel-mounted hose barb with clamp for 10mm (3/8in) OD. It will only fit a Koolance QD2 female shutoff valve.

## Description

---

Koolance (patent-pending) quick disconnect no-spill coupling with automatic shutoff. 6mm (1/4in) ID male panel-mounted hose barb with clamp for 10mm (3/8in) OD. It will only fit a Koolance QD2 female shutoff valve.

After pulling the ring on the female QDC side, the quick-disconnect fittings will separate. Liquid on both sides will be automatically obstructed with approximately 0.2mL freed. Fittings are nickel-plated brass. Maximum operating pressure is 2kgf/cm<sup>2</sup> (28.5 psi) @ 25°C. Maximum operating temperature is 100°C (212°F).

**ID:** 6mm (1/4")

**OD:** 10mm (3/8")

**Wall:** 2mm (5/64")

## Features

---

\*NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.\*

## Additional Information

---

Brand	Koolance
SKU	QD2-MS06-P
Weight	0.1000
Special Order	No
Fitting Type	Disconnect
Fitting Size	1/4"
Fitting Angle	Straight
Vendor SKU/EAN	829596909067

