





SilverStone Dual-Bay 3.5" RAID enclosure with USB 3.1 Type-C gen 2 - Black

\$174.99

Product Images





Short Description

SilverStone TS231U-C is an external hard drive enclosure made to accommodate 3.5" drives at speeds up to 10Gb/s with its USB 3.1 Gen2 capability and Type-C connector. This plug and play device is easy to setup with its tray-less design so users can quickly hot-swap drives on it in no time. A full range of RAID modes (RAID 0, 1, JBOD, Non-RAID) is supported to provide the best security and performance for installed hard drives. For enthusiasts or professionals requiring even greater performance, the TS231U-C is also equipped with UASP (USB Attached SCSI Protocol) so those with computers that support it can take their data transfer rate up another level.

Description

SilverStone TS231U-C is an external hard drive enclosure made to accommodate 3.5" drives at speeds up to 10Gb/s with its USB 3.1 Gen2 capability and Type-C connector. This plug and play device is easy to setup with its tray-less design so users can quickly hot-swap drives on it in no time. A full range of RAID modes (RAID 0, 1, JBOD, Non-RAID) is supported to provide the best security and performance for installed hard drives. For enthusiasts or professionals requiring even greater performance, the TS231U-C is also equipped with UASP (USB Attached SCSI Protocol) so those with computers that support it can take their data transfer rate up another level.

Features

- USB 3.1 Type-C connector with Gen2 up to 10Gb/s super speed transfer rate

- Configurable RAID function (RAID 0, RAID 1, JBOD, Non-RAID)
- Compact and screw-less design for easy HDD installation
- Supports UASP (USB Attached SCSI Protocol) function for even faster performance
- Aluminum body with Tool-free design
- Supports all 3.5-inch SATA drives up to any capacity
- Plug & play with support for hot-swapping

Specifications

Model No.	SST-TS231U-C
Color	Black
Material	Aluminum and SECC body
Cooling system	70mm x 15mm low noise fan x 1
Operating system support	Microsoft Windows 7 (32bit/64bit)*, 8/8.1/10 (32bit/64bit)** or future release version Mac OS 10.5*** or above
Power Supply	Internal universal power supply design Input: AC 100-240V, 50Hz / 60Hz Output: DC +12V / 4A
Drive support	3.5"
Enclosure interface	USB 3.1 Gen2 up to 10Gbps (Compatible with USB 3.0 / 2.0 / 1.1)
LED indicator	Solid blue: Power on Blinking blue: Read / Write Solid red: Rebuilding Blinking red: Drive not recognized
Chipset	ASM1352R A1, ASM1542
Driver interface support	SATA I / II / III
RAID mode support	RAID 0, RAID 1, JBOD, Non-RAID
Enclosure connector	USB 3.1 Type-C

Environment	Operating Temperature: 5°C ~ 35°C Operating Humidity: 20%RH ~ 80%RH Storage Temperature: -20°C ~ 50°C Storage Humidity: 20%RH ~ 80%RH
Net weight	1983±20g
Dimension	130mm (W) x 115mm (H) x 221.35mm (D) (without feet) 5.12" (W) x 4.53" (H) x 8.71" (D) (without feet)

Remark

- * If your OS version is Windows 7 or earlier, please install driver (available from SilverStone website) prior to using the TS231U-C.
- ** Windows 8 or 8.1, 10 supports TS231U-C automatically so you do not need to install additional driver for it.
- *** User should check for XHCI function in Mac OS, if computer system supports XHCI function then it can support TS231U-C automatically without additional driver installation.

Additional Information

Brand	SilverStone Technology
SKU	TS231U-C
Weight	2.0000
Color	Black
Device Type	External SSD/HDD Enclosure
Bay Size	Dual 3.5"/2.5" Bay
Vendor SKU/EAN	844761013363

