· WATERCOOLING · MODIFICATIONS ·

Performance-PCs.com

1701 R. J. Conlan Blvd.
NE, Unit #5
Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com
sales@performance-pcs.com

Like Us Facebook

See Our Instagram

Follow Us Twitter

Watch Our YouTube

SilverStone Dual 2.5" SATA 6 Gbit/s drives in one 5.25" drive bay

$224.99

Product Images

Short Description

To accommodate PC user's need for more storage flexibility and convenience, SilverStone created a line of front bay storage products called the FS series. Among the more unique products in the series, the FSR202 can support dual 2.5" SATA drives with release handle made for hot-swapping, thus exchanging drives is extremely quick and easy.

Description

To accommodate PC user's need for more storage flexibility and convenience, SilverStone created a line of front bay storage products called the FS series. Among the more unique products in the series, the FSR202 can support dual 2.5" SATA drives with release handle made for hot-swapping, thus exchanging drives is extremely quick and easy. It also has RAID 0 / 1 function with a user-friendly interface and independent LED indicators to let users quickly discern drive status. Finally for security, each drive tray is equipped with metal key lock. For those that need to upgrade their current PC with more drives with enhanced capability, SilverStone's FSR202 series is a great choice.

Features

- Fits two 2.5" SATA 6 Gbit/s drives in one 5.25" drive bay
- Individual metal key lock for each drive for extra security
- Configurable RAID 0 and RAID 1 modes
- Friendly LCD display with LED indicators for system monitoring during operation at all times
- Independent drive status LED
- Built-in cooling fan for excellent heat dissipation
- Compatible with all 2.5" drives up to 15mm thickness
- Fully supports SATA Hot-Swap function

Specifications

Model No.	SST-FSR202
Color	Black
Material	SGCC
Cooling system	40mm low noise fan
Form factor	5.25" drive bay x 1
RAID function	RAID 0 / RAID 1
Operating system support	Microsoft Windows 7 (32bit/64bit), 8/8.1/10 (32bit/64bit) or future release version Mac OS 10.5 or above
Controller	ASMedia 1092R

Electrical and Operating Requirements	Line Voltage: 12V / 5V DC Maximum Power Consumption: 30W Operating Temperature: 10°C ~ 35°C (50°F ~ 95°F) Storage Temperature: -20°C ~ 47°C (-4°F ~ 116°F) Relative Humidity: 5% ~ 95% non-condensing
Drive support	2 x 2.5" SATA HDD or SSD
Transfer rate	Up to 6 Gbit/s (dependent on drive speed)
LED indicator	Solid Purple: Fan Failure, Overheat (≥50°C), HDD Failure Solid Blue: Power, Read / Write, Rebuild Solid Red: Buzzer On
Driver interface support	SATA I / II / III
System monitoring	Fan Failure, Overheat, HDD / SSD Failure
Net weight	920g
Dimension	148mm (W) x 43mm (H) x 140mm (D) 5.83" (W) x 1.69" (H) x 5.51" (D)

Additional Information

Brand	SilverStone Technology
SKU	RL-FSR202
Weight	3.0000
Color	Black
Device Type	SSD/HDD Enclosure
Bay Size	Dual 3.5"/2.5" Bay
Vendor SKU/EAN	844761014070