



Nylon Fully-Insulated Female Disconnect, 22-18 AWG - Set of 4

\$1.29

Product Images



Short Description

Butted seam-construction prevents splitting under maximum pressure; Internal barrel serrations grip wires tightly to resist pull-out and reduce electrical resistance; Tin-plated brass construction for corrosion resistance; Wire range stamped on metal surface for easy interpretation; Shouldered barrel insulation quickly positions terminal for proper crimping; Expanded insulation entry accomodates a wide variety of insulation diameters and provides additional insulation support; Color coded for easy identification. Funnel entry on disconnect terminal quickly guides wires into crimp barrel and eliminates turned-back strands. Perfect for crimping on 18-22 guage wire for use with rocker switches or other terminal electrical devices.

Description

Butted seam-construction prevents splitting under maximum pressure; Internal barrel serrations grip wires tightly to resist pull-out and reduce electrical resistance; Tin-plated brass construction for corrosion resistance; Wire range stamped on metal surface for easy interpretation; Shouldered barrel insulation quickly positions terminal for proper crimping; Expanded insulation entry accomodates a wide variety of insulation diameters and provides additional insulation support; Color coded for easy identification. Funnel entry on disconnect terminal quickly guides wires into crimp barrel and eliminates turned-back strands. Perfect for crimping on 18-22 guage wire for use with rocker switches or other terminal electrical devices.

Includes:

Bag of 4 disconnects

Additional Information

SKU	SPADES
Weight	0.0500
Vendor SKU/EAN	EBTM-18-FDNFI-2218-C

