

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com



Follow Us Twitter







Akasa M.2 PCle and M.2 SATA SSD adapter card with RGB LED light and heatsink

\$26.95

Product Images













Short Description

The Akaa M.2 PCIe and M.2 SATA SSD adapter card heatsink has addressable RGB LED lights and supports M.2 drive lengths of 2230,2242,2260 and 2280.

Description

The Akaa M.2 PCIe and M.2 SATA SSD adapter card heatsink has addressable RGB LED lights and supports M.2 drive lengths of 2230,2242,2260 and 2280.

Features

- Illuminate M.2 SSDs with over 16.7 million colours
- PCB exposed copper coupled with an additional heatsink design reduces SSD heat and enhances performance
- Superior mechanical design for easy installation
- M.2 PCle 3.0 x 4 NVMe to PCle x 4 host adapter
- Easily fits in a PCle Gen3 x4, x8 or x16 slot
- Supports 5V addressable LED pin

Specifications

Application	Add addressable RGB LED lighting and cool M.2 PCle SSD and M.2 SATA SSD
Designed for	M.2 PCle/NVMe (M Key) SSD & M.2 SATA (B+M Key) SSD 2230, 2242, 2260, 2280 and 22110 M.2 form factor lengths 5V addressable RGB LED pin headers
Material	Metal bracket, printed circuit board, exposed copper, aluminium heatsink
Voltage rating for LED	5V DC
Current rating for LED	0.48A
Connector	3-pin addressable RGB connector 4-pin addressable RGB connector
Certification	Gigabyte RGB Fusion, MSI Mystic Light, ASUS AURA and AsRock Polychrome
Operating temperature	0°- 55° C
Operating system compatibility	OS independent; no additional drivers or software required
Contents	M.2 SSD to PCIe adapter card, silicon thermal pads (x2), 2.54mm 3-pin to RGB 4-pin male cable, 2-pin to RGB 4-pin female cable, mounting screws x 4, screwdriver, user manual
Product code	AK-PCCM2P-03

Additional Information

Brand	Akasa
SKU	AK-PCCM2P-03
Weight	1.0000
Color	Black
Card Function	SSD Adapter Card
Card Form Factor	PCI EXPRESS
Ports	PCIe Slot

