

Attractive and durable coated rust-resistant steel mounting bracket with mounting screws and washers.

Includes 3' Standard mini A to B USB communication cable.

Optional: Internal Mini A to USB 5-Row. This cable can be used with any display that features a Mini USB header and connect to a 4/5 pin internal motherboard USB header

*Matrix Orbital provides all manuals on line at our Tech Support site at <http://www.matrixorbital.ca/manuals/> and questions may be posted on our forum site at <http://www.lcdforums.com/forums>

Features

Display:

LK204-7T-1U-USB-TCI

- 5Vdc
- 20 Characters by 4 lines
- USB interface
- 7 key tactile keypad
- 3 Bi color LEDs
- Fits into a 1U opening

Mounting Bracket:

B19264-BK

Cables:

External Mini USB

Specifications

Display Appearance						
Character X Lines		Module Size			Character Size	
Length	Width	Thickness	Length	Width		
20	x	4	140.20 <i>m</i>	x	38.00 <i>mm</i> x 29.00 <i>mm</i>	5.20 <i>mm</i> x 3.90 <i>mm</i>
Display Size			Background Color		Text Color	
Length	Width	Black		Tri-Color		
82.00 <i>mm</i>	x	28.40 <i>mm</i>				
Features						
Keypad		One Wire		GPO		
7		N/A		6		

Interface

USB	Buffer	Other
19200 33600 56700	128	

Environmental Conditions

Standard Temp.		Extended Temp (-E)		Max Humidity
Min	Max	Min	Max	
0.00°C	to 50.00°C	-20.00°C	to 70.00°C	90.00 %

Power Requirements

Supply Current	Backlight Current	Inrush Current
90 mA	140 mA	N/A

Additional Information

Brand	Matrix Orbital
SKU	BLK204-7T-1U-BK-USB-TCI-D
Weight	3.0000
Color	Black
Device Type	Multi-purpose
Bay Size	5.25" Bay
Special Price	\$62.97

