

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com











# SYBA IDE SATA Hard Disk Drive Interface Converter, Bi-directional

\$6.99 was \$9.99

## **Product Images**







# **Short Description**

## **Product Details:**

Easily converts an IDE hard disk drive to be used on a SATA system or vice versa

#### Features:

- Unique Bi-directional SATA <- > IDE Converter
- Supports 3.5-inch SATA and IDE (ATA) Hard Drive
- Supports 5.25-inch SATA and IDE (ATA) Optical Drives
- Power-On and HDD-Activity LED Indicators
- Ultra Low Power Consumption
- Connectors:

- o IDE (ATA) Connector
- SATA host Connector (Yellow)
- SATA Device Connector (Black)
- 4-pin FDD Power Connector
- Two Independent Ultra ATA Channels with 128/256 Bytes Buffer Per Channel
- Plug & Play. No Driver installation Needed
- Serial ATA Interface Specifications:
  - o Complies with SATA 1.0a Specification
  - Supports SATA Generation 1 with Transfer Rate up to 1.5Gbps (150MB/s)
  - Supports Spread Spectrum in Receiver
  - o Supports SATA Power Saving Mode: Partial and Slumber
- IDE (ATA) Interface Specifications:
  - Complies with ATA Specification
  - Ocmplies with Ultra ATA 133 with Transfer Rate up to 133MB/s
  - Supports PIO Mode 0, 1, 2, 3, 4, 5, 6
  - Supports MDMA mode 0, 1, 2
  - o Supports Ultra DMA Mode 0, 1, 2, 3, 4, 5, 6
  - Supports Master/Slave/Cable Select Mode by Configuration Switches

#### Specifications:

• Dimension: L 6.5 x W 4.5 x H 1.5 inch

Weight: 0.2 lb

UPC: 893049000472

Requirement: Windows 98SE/ME/2000/XP Operating System

## Description

### **Product Details:**

Easily converts an IDE hard disk drive to be used on a SATA system or vice versa

#### Features:

- Unique Bi-directional SATA <- > IDE Converter
- Supports 3.5-inch SATA and IDE (ATA) Hard Drive
- Supports 5.25-inch SATA and IDE (ATA) Optical Drives
- Power-On and HDD-Activity LED Indicators
- Ultra Low Power Consumption
- Connectors:
  - O IDE (ATA) Connector
  - SATA host Connector (Yellow)
  - SATA Device Connector (Black)
  - o 4-pin FDD Power Connector
- Two Independent Ultra ATA Channels with 128/256 Bytes Buffer Per Channel
- Plug & Play. No Driver installation Needed
- Serial ATA Interface Specifications:
  - $^{\circ}\,$  Complies with SATA 1.0a Specification
  - o Supports SATA Generation 1 with Transfer Rate up to 1.5Gbps (150MB/s)
  - o Supports Spread Spectrum in Receiver

- o Supports SATA Power Saving Mode: Partial and Slumber
- IDE (ATA) Interface Specifications:
  - Complies with ATA Specification
  - $^{\circ}\,$  Complies with Ultra ATA 133 with Transfer Rate up to 133MB/s
  - $^{\circ}~$  Supports PIO Mode 0, 1, 2, 3, 4, 5, 6
  - O Supports MDMA mode 0, 1, 2
  - $^{\circ}~$  Supports Ultra DMA Mode 0, 1, 2, 3, 4, 5, 6
  - $^{\circ}\,$  Supports Master/Slave/Cable Select Mode by Configuration Switches

#### Specifications:

• Dimension: L 6.5 x W 4.5 x H 1.5 inch

Weight: 0.2 lbUPC: 893049000472

• Requirement: Windows 98SE/ME/2000/XP Operating System

## **Additional Information**

Brand	SYBA
SKU	SY-BIR-IDESA-D
Weight	2.0000
Cable Type	Multi-Media I/O Ports
Vendor SKU/EAN	893049000472
Special Price	\$6.99

