



EK-Torque HDC-16 - Black Nickel (3867)

\$7.49

Product Images





Short Description

EK-Torque HTC 16 fittings are EK's new minimalistic 16mm hard-tube compression fittings designed for use with solid tubing such as Acrylic and PETG. With a non-intrusive, yet striking look, and with NO added branding at all. They can be complemented by interchangeable aesthetic color rings, and are an ideal choice for anyone and a perfect match with EK-Quantum series products.

Description

EK-Torque HTC 16 fittings are EK's new minimalistic 16mm hard-tube compression fittings designed for use with solid tubing such as Acrylic and PETG. With a non-intrusive, yet striking look, and with NO added branding at all. They can be complemented by interchangeable aesthetic color rings, and are an ideal choice for anyone and a perfect match with EK-Quantum series products.

The locking ring prevents solid tube to be pulled out of the fitting by compressing the rubber gasket underneath the ring. The grooves on the outside allow for easier hand tightening. The compression ring has cutouts in EK Quantum signature shape allowing for the colored aesthetic ring to be shown. The colored rings are available in many colors and are screwed onto the fitting before the compression locking ring. The aesthetic rings are sold separately.

The fitting barb and the compression rings are covered with a unique, high-quality satin black finish. Both are made of CNC machined brass and the seal is made quality rubber O-rings. Black EK-Torque series fittings are intentionally not painted on the inside to reduce the level of possible pollutants in the loop.

The base fitting surface is smooth and has no adequate gripping surface, but the inside of the barb is socketed with a 9mm hex Allen key pattern. It's highly recommended to use an Allen Key 9mm (purchased separately) to prevent skin damage to the fingertips while installing the fitting. Please, be advised not to use excessive force when attaching fitting barbs using Allen Key 9mm in order to prevent damage to other liquid cooling products!

These fittings are guaranteed to be compatible with all other EK Water Blocks liquid cooling products.

Specifications

Technical data:

- Finish: Black Nickel
- Thread: G1/4" BSP; 4.5mm male thread length
- Supported tube: 16mm OD
- The outer diameter of a fitting: 24mm
- Installed height: 15mm
- Compatible solid tubing: Acrylic, PETG, Copper, Brass, Stainless Steel

Made in Europe - Slovenia!

PLEASE NOTE:

- Please wet the gasket (o-ring) using drops of water prior to installing the solid tube.
- Do not use excessive force when inserting solid tube!
- Do not use excessive force when attaching fitting barbs using Allen Key 9mm in order to prevent damage!
- It is mandatory to use a chamfer tool on the edges of the freshly cut solid tube in order to prevent gasket (o-ring) damage.
- This product should NOT be installed with any aluminum Fluid Gaming parts!
- EK strongly recommends the use of PETG inserts with the use of PETG tubes.
- The aesthetic rings are sold separately.

Additional Info

	G1/4
--	------

Additional Information

Brand	EK Waterblocks
SKU	EK-TORQUE-HDC-16-BKNK-D
Weight	0.1500
Special Order	No
Fitting Type	Rigid Compression
Fitting Size	16mm
Fitting Angle	Straight
Fitting Finish	Black Chrome
Vendor SKU/EAN	3831109813867

