



Thermaltake A2029 120X25MM Smart Case Fan II 95.22/ 35.43 CFM 45/ 25.5DBA - Sleeved

Special Price
\$7.95 was
\$16.95

Product Images



Short Description

Thermaltake has again raised the bar for high-performance cooling fan with the release of second version of Smart Case Fan II. From the release of Smart Case Fan I to Smart Case Fan II, combined units sold has surpassed the 10 million mark worldwide. Building on Thermaltake's best-selling Smart Case Fan Series cooling fans, Smart Case Fan II V.2.0 combines all the advanced features found on Smart Case Fan and Smart Case Fan II with a more daring color scheme. Smart Case Fan II V.2.0 will extend Thermaltake's currently line of standard 80mm to include 90mm and 120mm model. Additionally, PCI Speed Controller will be included with all models for easy access.

Fan cable is fully covered in nylon Techflex sleeving and premium heatshrink, colors of your choice.

Description

Thermaltake has again raised the bar for high-performance cooling fan with the release of second version of Smart Case Fan II. From the release of Smart Case Fan I to Smart Case Fan II, combined units sold has surpassed the 10 million mark worldwide. Building on Thermaltake's best-selling Smart Case Fan Series cooling fans, Smart Case Fan II V.2.0 combines all the advanced features found on Smart Case Fan and Smart Case Fan II with a more daring color scheme. Smart Case Fan II V.2.0 will extend Thermaltake's currently line of standard 80mm to include 90mm and 120mm model. Additionally, PCI Speed Controller will be included with all models for easy access.

Fan cable is fully covered in nylon Techflex sleeving and premium heatshrink, colors of your choice.

Features

- 3 functions in 1 fan
- Smart Case Fan II (3 functions in 1) :
 - Full speed when jumper on
 - Temperature control : Fan speed varies according to the temp detected by the sensor
 - Manual control : Adjust fan speed manually
- Smart Case Fan II series in 80, 90, 120mm dimensions
- 2 ball bearing, extend the operating life
- 3 to 4 pin adaptor included, to power supply unit
- Bundle with bracket controller, attach to PCI slot

Specifications

| | |
|-------------------|--|
| P/N | A2029 |
| Fan Dimension | 120x120x25 mm |
| Rated Voltage | 12V |
| Started Voltage | 7V |
| Rated Current | 0.08 ~ 0.50 A |
| Power Input | 0.96 ~ 6.00 W |
| FAN Speed | 130020% RPM at 20C ~ 350010% RPM at 55C |
| MAX. Air Pressure | 1.31 ~ 6.57 mmH2O |

| | |
|------------------|---|
| Max. Air Flow | 35.43 ~ 95.22 CFM |
| Noise | 25.5 dBA at 1300RPM ~ 45dBA at 3500RPM |
| Bearing Type | 2-Ball Bearing |
| Life Expectation | 50,000 Hours |
| Connector | 3 Pin |
| Weight | 140g |

Additional Information

| | |
|----------------|-------------|
| Brand | Thermaltake |
| SKU | A2029-D |
| Weight | 1.0000 |
| Color | Black |
| Fan Dimensions | 120mm |
| Fan Width | 25mm |
| Fan Connection | 3-Pin |
| Fan Voltage | 12 VDC |
| Fan RPM | 3500 |
| Fan CFM | 95 |
| Fan Noise (dB) | 45 |
| Special Price | \$7.95 |

