

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com













\$9.99

Product Images



Short Description

EK-HD Tube is solid type extruded acrylic tubing intended for use with EK-HD push-in adapters and EK-HDC series compression fittings.

The tubing may be heat treated to achieve certain bends. For expert users only!

Description

EK-HD Tube is solid type extruded acrylic tubing intended for use with EK-HD push-in adapters and EK-HDC series compression fittings. The tubing may be heat treated to achieve certain bends. For expert users only!

It is mandatory to chamfer the edges of freshly cut tube in order to prevent gasket (O-ring) damage. EK recommends a 0,5mm x 45° chamfer.

Specifications

Technical data:

Material: Extruded acrylic
Inner diameter: 10 mm
Outer diameter: 12 mm
Length: 500 mm (19.5")

The package contains 2 pieces of tube only. Please purchase EK-HD Adapter or EK-HDC compression fittings separately!

For easier installation we recommend wetting the gasket (O-ring) using drops of water prior to installing solid tube.

Additional Information

Brand	EK Waterblocks
SKU	EK-HARD-TUBE-12MM-0.5MM-2PCS
Weight	2.0000
Color	Clear
Tube Type	Acrylic
Tube Size	12mm
Vendor SKU/EAN	3831109835623

4/20/24

