



# Thermaltake Pacific R22

\$49.99

## Product Images





## Short Description

---

The R22 is a 300ml tube reservoir for PC water cooling, manufactured of high quality POM and PMMA material

## Description

---



## Pacific R22 Reservoir

Thermaltake introduces the Pacific R Series tube reservoirs for the ultimate in custom PC watercooling configurations. Featuring exceptional performance and unrivalled reliability, the R22 is manufactured from high quality POM and PMMA material to provide a crystal clear, high performance, durable solution. By giving users ideal mounting, fitting and flow, the R22 is the right choice for PC enthusiasts. Choose from: 120ml, 200ml, 300ml, and 500ml capacities, make your system a showcase for all to see with the Thermaltake Pacific R Series.

## Tt LCS Certified

Tt LCS Certified is a Thermaltake exclusive certification applied only to products that pass the design and hardcore enthusiasts standards that a true LCS chassis should hold to. The Tt LCS certification was created so that we at Thermaltake can indicate to all power users which chassis have been tested to be best compatible with extreme liquid cooling configurations, ensuring you get the best performance from the best features and fitment.



## Features

---



## Sturdy and Durable Design

Featuring 6mm thick of the pipe wall, Pacific R Series can sustain the maximum pressure up to 99 PSI (Pounds per square inch). Also, users can easily open out the top cap, cleaning the reservoir thoroughly.

## Maximized Compatibility

Made in Taiwan, with five predrilled G1/4" holes to maximize compatibility, top and bottom caps provide multiple options for placing the G1/4" fittings/barbs as inlet or outlet.



\*R33 water flow diagram



## Heat-resistant Acrylic Tank

The Pacific R Series Reservoirs are all made of reliable, light weighted POM and PMMA construction, which is crystal clear and highly durable. High quality acrylic (PMMA) tube maximum working temperature: 131°F (55°C).

## Easy and Flexible Application

Along with two brackets connected to both ends, Pacific R Series is solid hold inside the chassis and allows enthusiasts to build up superior water cooling system from an aesthetic standpoint and incorporate externally-modular upgrades for their chassis. The Pacific R Series can be installed either horizontally or vertically, making the chassis out of the ordinary!



# Specifications

## More Information

	CL-W076-PL00BL-A
	φ64 x 220 (H) (mm)
	450 g
	POM + PMMA
	300 ml
	1. Stopper *3 (G 1/4 ) 2. Bracket *2
	G 1/4

## Cautions

**Thermaltake recommends the following steps to be taken before using the Pacific series radiators and water blocks**

- To ensure a clean loop, flush and rinse your radiators and water blocks with distilled water prior to use.
- Do not use tap water or distilled water as your coolant, it may harm your loop and reduce performance.
- It is strongly recommended to use market proven pre-mix coolant, such as Thermaltake Coolant 1000. It offers great performance while protecting the entire liquid loop from corrosion.
- Before storing your water cooling components, please clean, rinse and dry. This will ensure a longer lifespan for your components.

**Thermaltake recommends the following steps to be taken after completing your water loop setup**

- It is strongly recommended to use market proven pre-mix coolant, such as Thermaltake Coolant 1000. It offers great performance while preventing the entire cooling system – copper, brass, nickel, aluminum, and steel – from corrosion.
- Fill the reservoir with coolant and cycle the power on and off several times while the pump pushing the coolant into the loop.
- DO NOT let the pump run dry, when there is no liquid entering the pump turn off your power immediately
- Fill the reservoir to the top as it will prevent air from going into the pump
- If necessary tilt the system slightly from side to side to bleed the air out of the loop.
- Place some paper towels under fittings and joining points to test for leaks.
- Run the loop with the fill port open for about 24 hours to completely bleed the air out of the loop.
- Before starting, flush out your system correctly to prevent any coolant or unwanted particles sticking to your tubes, radiators and other cooling components.
- Coolant might fade over time.

## Additional Information

---

Brand	Thermaltake
SKU	CL-002I-PLOOSW-A
Weight	1.0000
Color	Black
Reservoir Type	Tube Res
Tube Res Length	300mm

