



# Thermaltake Pacific G1/4 PETG Tube 45-Degree dual compression 12mm OD - Black

\$7.99

## Product Images



## Short Description

---

Finished in black-plated copper, the Pacific G1/4 PETG Tube 45-Degree dual compression 12mm OD fitting is designed for use with solid PETG tubing, allowing users to redirect the tube at a 45 degree angle for easier loop management.

## Description

---



## Thermaltake Pacific G1/4 PETG Tube 45-Degree dual compression 12mm OD – Black

Finished in black-plated copper, the Pacific G1/4 PETG Tube 45-Degree dual compression 12mm OD fitting is designed for use with solid PETG tubing, allowing users to redirect the tube at a 45 degree angle for easier loop management. With high-flow and leak-free design, Thermaltake takes every detail seriously. Make your system a showcase for all to see with high quality components from Thermaltake.



## Tt LCS Certified

Tt LCS Certified is a Thermaltake exclusive certification applied only to products that pass the design and hardware enthusiasts standards that a true LCS chassis should hold to. The Tt LCS certification was created so that we at Thermaltake can indicate to all power users which chassis have been tested to be best compatible with extreme liquid cooling configurations, ensuring you get the best performance from the best features and fitment.

## High-Flow and Leak-free Design

Committed to deliver the highest quality, the fitting includes six preinstalled O-rings and allows proper connection to G1/4" ports, securing properly to any cooling components while providing an even seal around the tubing.

For tubes:

- Outer diameter: 12mm



## Remarkable Expansion

Thermaltake offers a full line of Pacific Series components for enthusiasts to build up aesthetically-superior water cooling systems by incorporating externally-modular upgrades for their chassis.

## Cautions

Thermaltake recommends the following steps to be taken before using the Pacific series radiators and water blocks

1. To ensure a clean loop, flush and rinse your radiators and water blocks with distilled water prior to use.
2. Do not use tap water or distilled water as your coolant, it may harm your loop and reduce performance.
3. It is strongly recommended to use market proven pre-mix coolant, such as Thermaltake Coolant 1000. It offers great performance while protecting the entire liquid loop from corrosion.
4. Before storing your water cooling components, please clean, rinse and dry. This will ensure a longer lifespan for your components.

Thermaltake recommends the following steps to be taken after completing your water loop setup

1. It is strongly recommended to use market proven pre-mix coolant, such as Thermaltake Coolant 1000. It offers great performance while preventing the entire cooling system – copper, brass, nickel, aluminum, and steel – from corrosion.
2. Fill the reservoir with coolant and cycle the power on and off several times while the pump pushing the coolant into the loop.
3. DO NOT let the pump run dry, when there is no liquid entering the pump turn off your power immediately
4. Fill the reservoir to the top as it will prevent air from going into the pump
5. If necessary tilt the system slightly from side to side to bleed the air out of the loop.
6. Place some paper towels under fittings and joining points to test for leaks.
7. Run the loop with the fill port open for about 24 hours to completely bleed the air out of the loop.

# Specifications

---

## More Information

	CL-W144-CU00BL-A
	20 x 28 x 34.4 (H) (mm)
	41 g
	CU
	PETG Tube To PETG Tube
	OD : 12 mm

## Additional Information

---

Brand	Thermaltake
SKU	CL-W144-CU00BL-A
Weight	0.2000
Special Order	No
Fitting Type	Compression
Fitting Size	12mm
Fitting Angle	45 Degree
Fitting Finish	Matte Black

