

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com



Follow Us Twitter







# Barrow Pump integrated 240mm radiator-Black

\$129.99

## **Product Images**





## **Short Description**

The Barrow Pump integrated 240MM radiator water cooling devices is an All in One radiator

## Description

## DARIDP-30

Barrow Pump integrated radiator water cooling devices DARIDP-30





DARIDP-30



High lift pump



Red copper heat Standard fan 120MM dissipation modules



Easy to install

### Products information

Thread: DARIDP-30	Color: Black/silver
Quantity: 1Set	Thread: G1/4"
Structure: Pump+Radiator+Fan	Dimensions: Please refer to the dimension drawing
Application: Suitable for installation	n of integrated water-cooling system
Note: In case of product appearance	e structure upgrade, without further notice, in kind prevail

## **Features**

3

#### Integrate several products in one

integrates with pump, radiator, fan and reservoirs. It is highly integrated water-cool ing hardware, and suitable for ITX chassis to save internal space.



#### Equipped with 17W pump, has the strong power



Product parameter

Rated voltage: DC LDV
Rated current: LAA
Rated current: LTW
Temperature range: <80°C
Operating roles: <400bA
Saced resultation mode: PWM speed re

Maximum head pressure: 5-6M Maximum flow side: 560L/H Relational Spood: 4000rpm Service 8fe: >50000h

#### e enclosed fived heat sink ontimize the whole air channel

dopt the integrated fixed heat sink to fix the fan and radiator, and seal the gay be-



#### The optimized pump chamber structure

The pump shows excellent water movement by the pump chamber structure is designed



#### Dual mode speed regulation function

With PWM and manual dual speed control function, PWM temperature control automatispeed control can be used, or manual lineb can be used to achieve manual speed control manual line control of power consumption and manual bullons.

Ture electroise to turn on manual mode





#### New-type fan interface



#### Product parameter

Speed: 939-3900RPM.100
Rated vottage: 12V [10.8V-13:3
Rated current: 0.25A
Starting voltage: DC-EV
Function: PRM adjust speed
Rearing: Hydraulic bearing
15G-200988

oters

wifee: 33.92CFH-68.69CFM

Sound: 21.861(a)-32.261(a)

Connector: SPIN (PMM)

Long: S60em

Lighting: LRC2.0 lighting control system



Acrylic transparent windor The coolant level inside the radiator can be observed through the viewing window, and then the can will coolant in time.









Multi-directional water inlet madiator preset the multi-directional subor inlet, and many installation methods of radiator all can fill the logical and water quickly.







## Specifications

5

## **Appearance size**





DIMENSION IN MM

## Additional Information

Brand	Barrowch
SKU	DARIDP-30-240-BK
Weight	6.0000
Color	Black
Radiator Size	240 (2 x 120mm)
Radiator Thickness	30mm
Vendor SKU/EAN	6937826615252



7