

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com



Follow Us Twitter









\$151.99

Product Images





Short Description

Equipped with a total of eight G1/4" threaded connection ports, the EK-Quantum P Series X-Flow Surface radiators allow for an unbeatable combination of versatility and performance within the PC radiator market.

Description

Details

Equipped with a total of eight G1/4" threaded connection ports, the EK-Quantum P Series X-Flow Surface radiators allow for an unbeatable combination of versatility and performance within the PC radiator market. With the 44mm thickness, they still provide ample performance across the entire fan operational range, regardless of which crossflow port setup the user chooses. A total of sixteen 2mm wide copper tubes across the whole radiator length enable optimal coolant flow, putting no stress on your cooling loop. High-grade non-louvered copper fins with 18 FPI density provide the best balance between thermal transfer and air resistance for optimal performance even at low-speed fan operation. To maximize cooling performance, a Push/Pull setup can be utilized on any P X-Flow Series EK-Quantum Surface radiator.

Features

New and Improved

The EK-Quantum Surface P series radiator maximizes performance by utilizing a new radiator core. When comparing core to core performance, the Surface P radiator performs up to 10% better than its predecessor, the CoolStream PE, thanks to its enhanced fin structure and optimized core.

EK-Quantum Surface premium radiators are built upon years of development and market research to deliver the best product that the market demands in every possible way. The finish of the materials, mechanical rigidity, and performance have all been brought to another level. Like all other Quantum Line products, EK's brand new Surface radiators bring numerous performance improvements, including thermal performance, coolant flow restriction, and airflow restriction.

With the supplied screws, this radiator is compatible with 120mm fans that have a standard 25mm thickness. EK recommends using EK fans or similar ones with sealed-edge frames. This classic yet effective square shape of the fan casing provides optimal performance in either the pull (suction) or push (pressure) regime without any hydraulic losses, thus ensuring the optimal cooling capacity of your liquid cooling radiators.

Thick, extruded aluminum end caps with a contrasting silver finish give the radiator a premium look and feel. They cover the internals and join the stamp-pressed side plates, creating a rigid structure that is pleasant to handle. The stainless-steel side plates are coated with durable semi-gloss black paint, while the fins themselves have a special black matte coating with a high thermal conductivity coefficient.

Crossflow - Tube Routing With No Compromise

Set into the aluminum accent end caps are modular plugs and extenders that can be interchanged and configured by the user for optimal tube routing. This X-Flow multiport radiator has four G1/4" threaded connection ports on both ends of the radiator allowing for sixteen different ways of connecting In and Out tube routing.

M4 Screws - Standardized, Easy to Find

Hard-wearing black M4 Philips round-headed screws are supplied for ease of use. In general use case scenarios, EK strongly suggests using only the included screws to avoid damage to the radiator itself. However, M4 screw compatibility allows the users to source longer screws if necessary. The cooling core is designed to cause no detrimental damage to the structural integrity of the radiator core even if the customer uses longer screws accidentally, as they will collide only with the fins.

Easy Disassembly - DIY Modding Dream

The EK-Quantum Surface range was designed and executed as a modular product range rather than individually sized radiators. Such a design achieves immaculate fitment and continuity in appearance while at the same time making the disassembly process very easy and straightforward. Catering to the DIY modding community is something EK has always been supporting, so painting and modifying your Surface radiator will be a breeze.

Loop Friendly - Don't Worry About Your Pump

The internal structure design of the radiators was executed with low flow restriction in mind, providing no unnecessary stress on the rest of the cooling loop. This means you will be able to add multiple radiators to your cooling loop using only a single pump (D5 or DDC). The radiators are also airflow-friendly and low-restriction, allowing lower fan speed operation to achieve the same performance. Low airflow restriction keeps the case well ventilated and allows other radiators in the case to breathe properly.

EK-Matrix7 Compatible – For the Cleanest Tube Runs

Since any custom liquid-cooling loop is built from multiple EK products, the most valuable distinction in aesthetics and ease of use comes from the sum of all the parts. To address this, EK initiated Matrix7, a system that standardizes products' dimensions, as well as port position and spacing. In so doing, we are making the liquid cooling loop assembly more intuitive and having a clean set of parallel tubing runs easier than ever before.

All EK-Quantum Surface radiators are EK-Matrix7 compatible, which means they effortlessly integrate with Reflection², the second generation of Quantum distro plates. This enables the user to easily swap and upgrade between S, P, and X series Surface radiators within the same case (provided the case supports thicker radiators in the same position).

Specifications

Technical and Material Specifications:

- High-grade 99.9% copper fins
- Copper H90 tubing
- Brass H62 end tank chambers
- Stainless Steel side plates
- Extruded Aluminum Silver anodized end piece covers
- Brass nickel-plated extenders and plugs

Dimensions: 420 x 130 x 44mm (L x W x H)

Weight: 1.64kg

FPI: 18

Port threads: 8x G1/4"

Fan compatibility: 120x120x25mm fan

Pressure tested: 1bar

Enclosed:

- EK-Quantum Surface P series radiator

- 12x Phillips Slotted M4x30mm for 25mm thick fans
- 12x Phillips Slotted M4x5mm for mounting the radiator directly to the case
- 6mm steel Allen (Hex) key
- 9mm steel Allen (Hex) key

Designed and Engineered in Slovenia Made in China

PLEASE NOTE:

- Use of the improperly long screws may result in piercing of the radiator core and irreparably damage the product. Such misuse is not covered by the product warranty!
- This product should NOT be installed with any aluminum parts!

Additional Info

G1/4
3
120mm

Additional Information

EK Waterblocks
EK-QTM-SURF-P360M-XF-WH
5.5000
White
360 (3 x 120mm)
44mm
3831109839225

