


Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222






\$78.95



www.performance-pcs.com sales@performance-pcs.com

# Alphacool Alphacool VPP Apex Pump

## **Product Images**





## Short Description

The Alphacool Apex VPP is a powerful pump that is compatible with the most popular D5/VPP tops and reservoirs. Via the 4-pin fan connector, the speed of the pump can be read and controlled via PWM signal. The Apex VPP is supplied with power via the SATA connector.

## Description

The Alphacool Apex VPP is a powerful pump that is compatible with the most popular D5/VPP tops and reservoirs. Via the 4-pin fan connector, the speed of the pump can be read and controlled via PWM signal. The Apex VPP is supplied with power via the SATA connector.

### Features

#### Features

Alphacool's Apex VPP doesn't use a spherical bearing and relies on a ceramic axle. The motor's coils have been moved from the inside to the outside. These changes have the effect that the pump is fundamentally more stable and smoother running, and any vibrations that arise have been significantly reduced. Another positive side effect is that power consumption has been almost halved as a result.

#### Power supply

Compared to Alphacool's Eispumpe, the power is not supplied via a 4-pin Molex connector. Instead, the Apex VPP pump is connected to the power supply using a SATA connector.

#### Control

The Apex VPP pump has a 4-pin fan connector that connects to the motherboard or to an external controller. This allows you to control the speed range of the pump via PWM and read out the RPM signal.

## Specifications

Technical data		
Dimensions (L x W x H)		65 x 65 x 41mm
Material pump		synthetic material
Material pump cover		aluminium
Material axle		ceramics
Connections		4-Pin PWM   SATA
Rotational speed		2500 - 4500 RPM
Cable lengths		4-Pin PWM - 48cm   SATA - 48cm
Operating voltage		8-13V DC / 14W IP32
Starting voltage		12V DC
Maximum pumping head		4,25m
Maximum flow rate		340L/h
Maximum working temperate	ure	60°C
Weight		276g
Color		black
Color:	blacl	K
Material:	Plastic, Aluminium, Ceramic	
Manufacturer:	Alphacool	
Approved fluids:	Water, Water/ glycol mixture	
Voltage:	12V DC	
Water inlet:	Not available	
Water outlet:	Nota	available
	Dimensions (L x W x H) Material pump Material pump cover Material axle Connections Rotational speed Cable lengths Operating voltage Starting voltage Maximum pumping head Maximum flow rate Maximum working temperat Weight Color echnical details Color: Material: Manufacturer: Approved fluids: Voltage: Water inlet:	Dimensions (L x W x H) Material pump Material pump cover Material axle Connections Rotational speed Cable lengths Operating voltage Starting voltage Maximum pumping head Maximum flow rate Maximum flow rate Maximum working temperature Weight Color Veight Color: blact Material: Plast Manufacturer: Alph Approved fluids: Wate Voltage: 12V Water inlet: Not a

Max. System temperature:	60°C
Possible control range:	8-13V DC
Power input:	14W
Max. Discharge head:	4,25m
Max. Flow:	340 L/h
Dimensions:	65 x 65 x 41mm
Power connector:	SATA

Note on application

Please use only in conjunction with clear transparent water cooling fluids. The particles and additives in Pastel liquids can clog and permanently damage water cooling products such as radiators, pumps, coolers and hoses. This can result in voiding the manufacturer's warranty as well.

## Additional Information

Brand	Alphacool
SKU	AC-13339
Weight	1.5000
Color	Black
Vendor SKU/EAN	4250197133395

