



Lian Li CR-25A Aluminum USB 2.0 Card Reader 20 in 1 - Silver

\$21.95

Product Images



Short Description

The Lian Li CR-25 Card Reader is designed for internal or external use to match the user's demands. The card reader works with high speed data transfer rates up to 400 MB/sec using a USB 2.0 port. For internal use the reader can be mounted in a 3.5" drive bay. The power is supplied via the USB port. Install the CR-25 into your computer's 3.5" drive bay and enjoy a fast, easy way to

transfer data from your computer to the most common 20+ different types of memory cards. The casing of this card reader is made out of brushed aluminum and matches all Lian Li cases.

Description

The Lian Li CR-25 Card Reader is designed for internal or external use to match the user's demands. The card reader works with high speed data transfer rates up to 400 MB/sec using a USB 2.0 port. For internal use the reader can be mounted in a 3.5" drive bay. The power is supplied via the USB port. Install the CR-25 into your computer's 3.5" drive bay and enjoy a fast, easy way to transfer data from your computer to the most common 20+ different types of memory cards. The casing of this card reader is made out of brushed aluminum and matches all Lian Li cases.

Features

- Color Options: Silver or Black
- Connects via internal USB 1.1 or 2.0 cable
- High speed up to 480Mbit/sec
- Windows and Mac OS compatible
- Emission/Safety: FCC Class B, CE
- Power supply: USB port
- Connects to motherboard USB pin headers OR to the external USB Type A port.

Specifications

- * Four sockets support :
CF Slot : CF I, CF II, IBM Microdrive, Magic Store
SM Slot: SM, XD, XD-H, XD-M
MS Slot: MS, MS Duo, MS PRO, MS PRO Duo, MS PRO HS, MS PRO Duo HS.
SD Slot : SD, SD1.1, SD2.0, SDHC, MMC, RS-MMC, MMC Plus.
- * Support All cards without adaptor.
- * Support All cards without adaptor.
- * Two active LED indicators of power and busy (read/write) equipped.

- * Support USB2.0 Hi-Speed (480Mbps) Model/USB 1.1 Full-Speed (12Mbps) Model.

- * USB powered; no external power required.

- * USB transfer rate :
USB2.0 High-Speed 480MB/Sec
USB1.1 Full-Speed at 12MB/sec.

- * Card Data transfer rate : 700~4000Kb/s Max.

- * Internal USB Rev. 2.0 / 1.1. device

- * Operating temperature : 0° ~85°

- * Storage temperature: -40° ~150°

- * Relative Humidity: Operating RH: 50% Storage RH: 95%(Max without condensing)

- * Runs at 12MHz crystal.

Requirements:

- * OS : WindowsME/2000/XP and Mac OS X; Windows 98/2000(SP1/SP2) and Mac OS 9 drivers are compatible.

* Compatible with IBM PC and Mac PC

* USB Host card or USB Hub device

Dimensions:

* 102mm x 25mm x 60mm (W,H,D)

Additional Information

Brand	Lian-Li
SKU	CR-25A
Weight	1.0000
Color	Silver
Device Type	Card Reader
Bay Size	3.5" Bay

