



Koolance QDC (High Flow) Shutoff Nozzle, Male Panel Barb [10mm, 3/8"]

Special Price
\$6.39 was
\$7.99

Product Images



Short Description

Product Details:

Koolance (patent-pending) quick-disconnect shutoff valve. 10mm (3/8") ID male panel-mounted hose barb with clamp. It will fit any Koolance VL3 High Flow female shutoff valve.

Koolance's new VL2 & VL3 quick disconnects offer easier connection and disconnection than previous VLV models. The internal flow characteristics have also been improved. For compactness, VL2 has a smaller profile (and therefore smaller internal diameter) than VL3.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.5-1 mL freed. Nozzles are nickel-plated brass.

Description

Product Details:

Koolance (patent-pending) quick-disconnect shutoff valve. 10mm (3/8") ID male panel-mounted hose barb with clamp. It will fit any Koolance VL3 High Flow female shutoff valve.

Koolance's new VL2 & VL3 quick disconnects offer easier connection and disconnection than previous VLV models. The internal flow characteristics have also been improved. For compactness, VL2 has a smaller profile (and therefore smaller internal diameter) than VL3.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.5-1 mL freed. Nozzles are nickel-plated brass.

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

Brand	Koolance
SKU	VL3-M10B-P-D
Weight	0.2000
Special Order	No
Fitting Type	Disconnect
Fitting Size	3/8"
Fitting Angle	Straight
Special Price	\$6.39

