



Koolance Swiveling Elbow Fitting (Low Profile), Single

\$11.99

Product Images



Short Description

NZL-LXG2 is a special lower-profile fitting than [NZL-LXG1](#) at only 2cm (0.79") high.

Create a swiveling 90 degree elbow bend using any Koolance G 1/4 threaded nozzle. For a basic elbow fitting, the [Koolance Coupling Adapter](#) could also be used. Or for maximum adjustment, consider placing two swiveling elbow fittings together. Nickel-plated brass. Nozzle not included.

Description

NZL-LXG2 is a special lower-profile fitting than [NZL-LXG1](#) at only 2cm (0.79") high.

Create a swiveling 90 degree elbow bend using any Koolance G 1/4 threaded nozzle. For a basic elbow fitting, the [Koolance Coupling Adapter](#) could also be used. Or for maximum adjustment, consider placing two

swiveling elbow fittings together. Nickle-plated brass. Nozzle not included.

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Specifications

General

Weight	0.09 lb (0.04 kg)
Fitting Thread	G 1/4 BSPP
Materials	Brass, EPDM
Max Pressure @ 25°C	8kgf/cm2 (113.8psi)
Max Temp. Operating Tolerance	100°C (212°F)

Additional Information

Brand	Koolance
SKU	NZL-LXG2
Weight	0.0500
Special Order	No
Fitting Type	Adapter
Fitting Angle	90 Degree
Fitting Finish	Chrome
Vendor SKU/EAN	829596901221

