



Swiftech MCRES-MICRO Rev. 2 Reservoir

\$25.95

Product Images



Short Description

The MCRES Micro Revision 2 reservoir shares all the good things that characterized the classic MCRES Micro in size, quality, and provided accessories, but it also includes additional enhancements and functionalities that have been requested by enthusiast users.

Description

The MCRES Micro Revision 2 reservoir shares all the good things that characterized the classic MCRES Micro in size, quality, and provided accessories, but it also includes additional enhancements and functionalities that have been requested by enthusiast users:

- The most noticeable feature is an additional port at the bottom of the unit. This port can be used as follows:
 - o as an alternate outlet providing a straight tube routing to a pump located underneath
 - o to feed a second pump
 - o to plug-in a temperature sensor
 - o as a drain
- All threads, including the fill-port which was previously a PG7 standard, are now 1/4" BSPP (G1/4) compatible
- New 1/4" BSPP (G1/4) plugs made of high polish chrome plated brass, are used for both the fill-port and the alternate outlet port.
- A vent was added to the anti-turbulence baffle to eliminate the formation of a small air bubble that occurred in the previous model.

Features

In conjunction with the release of the MCRES Micro Revision 2, new fittings are now available to complement and enhance the use of this product:

- 1/4" BSPP(G1/4) to 1/2" barb high-polish chrome plated brass fill-port fitting: specially designed to fit inside of the fill-port or alternate outlet cavity of the MCRES Micro Rev 2 and to facilitate the use of a 5/8" socket to fasten the fitting



1/4" BSPP-1/2" RPF

- 1/2" Remote fill-port fitting: this type of panel mount fitting allows users to fill-up or refill their system from outside of the PC, or can alternatively be used as a drain; the fitting connects with 1/2" tubing to either the MCRES Micro Fill-port barb fitting (described above) or to a T-Line. Two models are available, black anodized aluminum body, or high polish chrome plated brass body. The high-polish chrome plated brass plug conveniently protrudes from the flange of the fitting for frequent access, and can be fastened either with a flat screw driver or a 5/8 socket. A standard 5/8" bimetal hole saw is all it takes to drill the panel and install the fitting.



1/2" FPF-AL
Black anodized
aluminum body

1/2" FPF-CPB
High Polish Chrome
plated brass body

Picture Gallery



The MCRES Micro with included black nylon fittings, and optional fill-port barb installed on top



The MCRES Micro with included black nylon fittings, included brackets, and optional fill-port barb installed to the alternate outlet



Same as above, with Optional chrome plated brass 1/2" fitting



A third party temperature sensor with 1/4" BSPP threads can easily be installed to the alternate outlet.

Specifications

0

Additional Information

Brand	Swiftech
SKU	MCRES-MICRO-REV2
Weight	2.0000
Color	Clear
Reservoir Type	Free Standing Tank
Vendor SKU/EAN	877790000639

