



Koolance QDC (Extreme Flow) Shutoff Nozzle, Female Comp.[ID:16mm (5/8"); OD:19mm (3/4")

Special Price
\$8.79 was
\$10.99

Product Images



Short Description

Koolance (patent-pending) quick-disconnect shutoff valve. 16mm (5/8") ID, 19mm (3/4") OD female straight connection with compression fitting. It will fit any Koolance VL4 Extreme Flow male shutoff valve.

Description

Koolance (patent-pending) quick-disconnect shutoff valve. 16mm (5/8") ID, 19mm (3/4") OD female straight connection with compression fitting. It will fit any Koolance VL4 Extreme Flow male shutoff valve.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.5-1mL freed. Nozzles are nickel-plated brass, silicone o-rings.

OD: 19mm (3/4")

ID: 16mm (5/8")

Wall: 1.5mm (1/16")

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

Brand	Koolance
SKU	VL4-F16-19S-D
Weight	0.2000
Fitting Type	Disconnect
Fitting Size	5/8" x 3/4"
Fitting Angle	Straight
Special Price	\$8.79

