



STARDOM i302-1S-WBS2 Aluminum 3.5" USB & 1394a & 1394b & eSATA External Enclosure

\$114.99

Product Images





Short Description

Product Details:

iTANK goes QUAD!!

The All New iTANK i302 now available in 3G eSATA, Firewire 400 & 800 and USB 2.0 host connectivity!

Features:

Hassle free drive installation and removal.

Available with removable hard drive trays, installing or removing a drive would be absolutely hassle-free with the iTANK. Each drive tray is equipped with a locking mechanism to securely lock the drive into place and avoid accidental removals in keeping your data safe.



Made with aluminum.

With its sleek exterior and finish, the iTANK is structured with an aluminum body with vent at the sides, this allows it to dissipate heat faster, keeping the enclosed drive to be comfortably operated.

Multi purpose connections

The iTANK is equipped with an eSATA port that provides faster performance in data read/write and USB2.0 port that brings convenience when the eSATA isn't available. The iTANK is compact in size for any desktop environment, never taking up too much space. When it's necessary to transfer large files (supports up to 1.5TB) from PC to PC, it's small enough to be made portable.



Applications:

It's Time Machine friendly!
 Yes! The iTANK i302 is capable of supporting the Time Machine included in the Mac OS X Leopard. Through any interface connections provided by the i302, all of your Time Machines files can be backed up speedily.



Bringing you data mobility.
 If you work between home and the office and have gigabytes of data that needs to be mobile, simply remove the hard drive and then insert it to another iTANK and be up and running.

Help you to manage your digital libraries.
 With the digital snapshots or videos taken, the MP3s or MPEGs that you have downloaded, you can easily manage them by saving them into different hard drives. With the iTANK you can archive all of your data with one simple enclosure but multiple drives thanks to the removable drive design to help you in organizing your libraries for music, videos, photos, etc.



Multi operating system application
 If your system is capable of booting from an external storage system, you can utilize the iTANK as your boot drive where you can switch to a different OS on different hard drives with the removable drive function.

Specifications:

iTANK Series	
Model No.	i302-1S-WBS2
Certifications	CE, FCC
Case Material	Aluminium a brick for optimised heat dissipation
Host Interface / Ports	<ul style="list-style-type: none"> • 1x e-SATA port (7pin) • 2x FireWire 800 ports (9pin) • 1x FireWire 400 port (6pin) • 1x USB 2.0 High Speed port, (USB B type 4pin)
Compatible Drive	3.5" SATA-II 3.0Gb/s hard drive (backward compatible 1.5Gb/s) Supports large volumes in excess of 2TB
Features	<ul style="list-style-type: none"> • Quad interface e-SATA / FireWire 800 / FireWire 400 / USB 2.0 • Hassle free drive installation and removal • Fanless

Data Transfer	e-SATA up to 3.0Gbps (300MB/s) FireWire 800 (1394b) up to 800Mbps (100MB/s) FireWire 400 (1394a) up to 400Mbps (50MB/s) USB 2.0 up to 480Mbps, (60MB/s) backward compatible USB 1.1
System Requirements (PC)	<ul style="list-style-type: none"> • e-SATA: Windows XP/Vista • FireWire 800 (1394b): Windows XP/Vista • FireWire 400 (1394a): Windows XP/Vista • USB 2.0: Windows XP/Vista
System Requirements (Mac)	e-SATA: Mac OS 10.4 or higher FireWire 800 (1394b): Mac OS 10.2 or higher FireWire 400 (1394a): Mac OS 10.2 or higher USB 2.0: Mac OS 10.2 or later
System Environment	<ul style="list-style-type: none"> • Operating Temperature: 5°C ~ 40°C • Operating Humidity: 20%RH ~ 80%RH • Storage Temperature: -20°C ~ 70°C • Storage Humidity: 10%RH ~ 90%RH
Power Supply	External Power Adapter universal auto-switching (UL, cUL, TUV, CE, FCC, PSB, BSMI, EK/Mark) Input: AC 100-240V, 1.2A, 50-60Hz Output: DC +12V/2A, +5V/2A
Product Size	• 222mm x 125mm x 35mm
Gross weight	1.6 kg
Packing	• Retail Box Size: 283 mm x 162 mm x 87 mm
Packing Accessories	With removable drive tray enclosed USB 2.0 cable (A type to B type) e-SATA cable (7pin to 7pin) FireWire 800 cable (9pin to 9pin) FireWire 400 cable (6pin to 6pin) External Power Adapter Power cord Manual

Description

Product Details:


iTANK goes QUAD!!

The All New iTANK i302 now available in 3G eSATA, Firewire 400 & 800 and USB 2.0 host connectivity!

Features:

Hassle free drive installation and removal.

Available with removable hard drive trays, installing or removing a drive would be absolutely hassle-free with the iTANK. Each drive tray is equipped with a locking mechanism to securely lock the drive into place and avoid accidental removals in keeping your data safe.



Made with aluminum.

With its sleek exterior and finish, the iTANK is structured with an aluminum body with vent at the sides, this allows it to dissipate heat faster, keeping the enclosed drive to be comfortably operated.

Multi purpose connections

The iTANK is equipped with an eSATA port that provides faster performance in data read/write and USB2.0 port that brings convenience when the eSATA isn't available. The iTANK is compact in size for any desktop environment, never taking up too much space. When it's necessary to transfer large files (supports up to 1.5TB) from PC to PC, it's small enough to be made portable.



Applications:

It's Time Machine friendly!
 Yes! The iTANK i302 is capable of supporting the Time Machine included in the Mac OS X Leopard. Through any interface connections provided by the i302, all of your Time Machines files can be backed up speedily.



Bringing you data mobility.
 If you work between home and the office and have gigabytes of data that needs to be mobile, simply remove the hard drive and then insert it to another iTANK and be up and running.

Help you to manage your digital libraries.
 With the digital snapshots or videos taken, the MP3s or MPEGs that you have downloaded, you can easily manage them by saving them into different hard drives. With the iTANK you can archive all of your data with one simple enclosure but multiple drives thanks to the removable drive design to help you in organizing your libraries for music, videos, photos, etc.



Multi operating system application
 If your system is capable of booting from an external storage system, you can utilize the iTANK as your boot drive where you can switch to a different OS on different hard drives with the removable drive function.

Specifications:

iTANK Series	
Model No.	i302-1S-WBS2
Certifications	CE, FCC
Case Material	Aluminium a brick for optimised heat dissipation
Host Interface / Ports	<ul style="list-style-type: none"> • 1x e-SATA port (7pin) • 2x FireWire 800 ports (9pin) • 1x FireWire 400 port (6pin) • 1x USB 2.0 High Speed port, (USB B type 4pin)
Compatible Drive	3.5" SATA-II 3.0Gb/s hard drive (backward compatible 1.5Gb/s) Supports large volumes in excess of 2TB
Features	<ul style="list-style-type: none"> • Quad interface e-SATA / FireWire 800 / FireWire 400 / USB 2.0 • Hassle free drive installation and removal • Fanless

Data Transfer	e-SATA up to 3.0Gbps (300MB/s) FireWire 800 (1394b) up to 800Mbps (100MB/s) FireWire 400 (1394a) up to 400Mbps (50MB/s) USB 2.0 up to 480Mbps, (60MB/s) backward compatible USB 1.1
System Requirements (PC)	<ul style="list-style-type: none"> • e-SATA: Windows XP/Vista • FireWire 800 (1394b): Windows XP/Vista • FireWire 400 (1394a): Windows XP/Vista • USB 2.0: Windows XP/Vista
System Requirements (Mac)	e-SATA: Mac OS 10.4 or higher FireWire 800 (1394b): Mac OS 10.2 or higher FireWire 400 (1394a): Mac OS 10.2 or higher USB 2.0: Mac OS 10.2 or later
System Environment	<ul style="list-style-type: none"> • Operating Temperature: 5°C ~ 40°C • Operating Humidity: 20%RH ~ 80%RH • Storage Temperature: -20°C ~ 70°C • Storage Humidity: 10%RH ~ 90%RH
Power Supply	External Power Adapter universal auto-switching (UL, cUL, TUV, CE, FCC, PSB, BSMI, EK/Mark) Input: AC 100-240V, 1.2A, 50-60Hz Output: DC +12V/2A, +5V/2A
Product Size	• 222mm x 125mm x 35mm
Gross weight	1.6 kg
Packing	• Retail Box Size: 283 mm x 162 mm x 87 mm
Packing Accessories	With removable drive tray enclosed USB 2.0 cable (A type to B type) e-SATA cable (7pin to 7pin) FireWire 800 cable (9pin to 9pin) FireWire 400 cable (6pin to 6pin) External Power Adapter Power cord Manual

Additional Information

SKU	i302-1S-WBS2
Weight	4.0000
Device Type	External SSD/HDD Enclosure
Bay Size	3.5" Bay

