



Koolance Radiator, 2x140mm, Copper (High Flow) [no nozzles]

\$76.49

Product Images



Short Description

The copper core HX-CU-1402V is designed for two 140mm fans. With a high fin density of 30 FPI (fins per inch), it offers best performance at higher air flow. Vertical (perpendicular) G 1/4 BSP threaded nozzle sockets, dual pass, 30mm (1.18") long mounting screws included.

Description

The copper core HX-CU-1402V is designed for two 140mm fans. With a high fin density of 30 FPI (fins per inch), it offers best performance at higher air flow. Vertical (perpendicular) G 1/4 BSP threaded nozzle sockets, dual pass, 30mm (1.18") long mounting screws included.

Specifications

| | |
|-----------------------------|---|
| Model | HX-CU1402V |
| Materials | Copper Fins, Brass Pipes |
| Tubing Size, ID | (Any) |
| Product Dimensions WxHxD | 5.5" x 12.4" x 1.2" (14cm x 31.6cm x 3.1cm) |
| Product Weight | 1.6 pounds (726g) |

Additional Information

| | |
|--------------------|-----------------|
| Brand | Koolance |
| SKU | HX-CU1402V |
| Weight | 2.0000 |
| Color | Black |
| Radiator Size | 280 (2 x 140mm) |
| Radiator Thickness | 31mm |

