



Koolance QDC (Extreme Flow) No-Spill, Male Threaded G 3/8

\$11.99

Product Images



Short Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. G 3/8 BSP threaded male nozzle for

screwing directly into a water block or other component of same threading. It will only fit any Koolance VL4N Extreme Flow female shutoff valve.

Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. G 3/8 BSP threaded male nozzle for screwing directly into a water block or other component of same threading. It will only fit any Koolance VL4N Extreme Flow female shutoff valve.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.2mL freed. Nozzles are nickel-plated brass..

Please note: The "VL2N" and "VL3N" are no-spill versions of current shut-off QDC nozzles. Be sure not to mix series (VL2, VL3, VL4, VL2N, VL3N) when connecting, as all are physically different from one another.

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

Brand	Koolance
SKU	VL4N-MG-D
Weight	0.2000
Fitting Type	Disconnect
Fitting Angle	Straight

