



Koolance QDC (Extreme Flow) No-Spill, Female Panel Barb [For ID: 16mm, 5/8"]

\$12.99

Product Images



Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. 16mm (5/8") ID female panel-mounted hose barb with clamp. It will only fit any Koolance VL4N Extreme Flow male shutoff valve.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.2mL freed. Nozzles are nickel-plated brass.

OD: 19mm (3/4")
ID: 16mm (5/8")
Wall: 1.5mm (1/16")

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

Brand	Koolance
SKU	VL4N-F16-19B-D
Weight	0.2000
Special Order	No
Fitting Type	Disconnect
Fitting Size	5/8"
Fitting Angle	Straight

