



Koolance QDC (Extreme Flow) No-Spill, Male Panel Barb [For ID: 16mm, 5/8"]

Special Price
\$9.59 was
\$11.99

Product Images



Short Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. 16mm (5/8") ID male panel-mounted hose barb with clamp. It will only fit any Koolance VL4N Extreme Flow female shutoff valve.

Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. 16mm (5/8") ID male panel-mounted hose barb with clamp. It will only fit any Koolance VL4N Extreme Flow female shutoff valve.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.2mL freed. Nozzles are nickel-plated brass.

OD: 19mm (3/4")
ID: 16mm (5/8")
Wall: 1.5mm (1/16")

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

| | |
|---------------|----------------|
| Brand | Koolance |
| SKU | VL4N-M16-19B-D |
| Weight | 0.2000 |
| Fitting Type | Disconnect |
| Fitting Size | 5/8" |
| Fitting Angle | Straight |
| Special Price | \$9.59 |

