



Koolance QDC (Low Profile) No-Spill Shutoff, Female Angle [For ID: 06mm, 1/4"]

Special Price
\$10.39 was
\$12.99

Product Images



Short Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. 6mm (1/4") ID female swiveling elbow

connection with compression fitting. It will only fit any Koolance VL2N male shutoff valve.

Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. 6mm (1/4") ID female swiveling elbow connection with compression fitting. It will only fit any Koolance VL2N male shutoff valve.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.2mL freed. Nozzles are nickel-plated brass. Maximum operating pressure is 5kgf/cm² (71 psi). Maximum operating temperature is 90°C.

OD: 10mm (3/8")
ID: 6mm (1/4")
Wall: 2mm (5/64")

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

Brand	Koolance
SKU	VL2N-F06L-D
Weight	0.2000
Fitting Type	Disconnect
Fitting Size	1/4"
Fitting Angle	90 Degree
Special Price	\$10.39

