



 **Koolance Gender
Changer, QDC (High Flow)
No-Spill Shutoff, Male/Male**

Special Price
\$10.07 was
\$12.59

Product Images



Description

Koolance male/male gender changer for (patent-pending) quick-disconnect no-spill shutoff valves. It will only fit any Koolance

VL3N female shutoff valve.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only 0.2mL freed. Nozzles are nickel-plated brass. Maximum operating pressure is 6kgf/cm² (85 psi). Maximum operating temperature is 90°C.

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

Brand	Koolance
SKU	ADT-VL3NMM-D
Weight	0.2000
Special Order	No
Fitting Type	Disconnect
Fitting Angle	Straight
Vendor SKU/EAN	829596905250
Special Price	\$10.07

