


Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222





www.performance-pcs.com sales@performance-pcs.com

\$3.95

Adaptor Revolvable G1/4' to G1/4' IG - Black Nickel

Product Images



Short Description

Product Details:

45° angled fittings are not only extremely useful but also look great!

Due to its low height of just 2cm this fitting is incredibly versatile. It is even possible to connect multiple of these connectors to lay a connector around corners. Due to its G1/4" inner thread the adapter is compatible to almost all fittings on the market! the revolvable joint can be rotated freely (360°). The joint is also equipped with a seal to avoid any leakage. Additionally the design of the adapter does not create any additional flow resistance.

Technical details: Material: Black Nickel brass Fitting sizes: Inner thread: G1/4" ; Outer thread: G1/4"

Extent of delivery: Angled 45° adapter revolvable G1/4" outer thread to G1/4" inner thread

Note: Due to the low depth of the connector threads of only 5mm, for some fittings spacer rings (Art.No: 14087, 1415 or 95008) are required for installation.

To ensure a perfect seal at the inner thread we recommend Teflon tape (Art.No. 32002) or an O-ring seal (Art.No. 95002)

Product Details:

45° angled fittings are not only extremely useful but also look great!

Due to its low height of just 2cm this fitting is incredibly versatile. It is even possible to connect multiple of these connectors to lay a connector around corners. Due to its G1/4" inner thread the adapter is compatible to almost all fittings on the market! the revolvable joint can be rotated freely (360°). The joint is also equipped with a seal to avoid any leakage. Additionally the design of the adapter does not create any additional flow resistance.

Technical details: Material: Black Nickel brass Fitting sizes: Inner thread: G1/4" ; Outer thread: G1/4"

Extent of delivery: Angled 45° adapter revolvable G1/4" outer thread to G1/4" inner thread

Note: Due to the low depth of the connector threads of only 5mm, for some fittings spacer rings (Art.No: 14087, 1415 or 95008) are required for installation.

To ensure a perfect seal at the inner thread we recommend Teflon tape (Art.No. 32002) or an O-ring seal (Art.No. 95002)

Additional Information

Brand	Phobya
SKU	PH-64084
Weight	0.1000
Fitting Angle	45 Degree
Vendor SKU/EAN	4049469057534

