



Koolance Swiveling Angle Fitting, Single - Black

\$11.99

Product Images



Short Description

Create a swiveling 90 degree elbow bend using any Koolance G 1/4 threaded nozzle. For a basic elbow fitting, the Koolance Coupling Adapter could also be used. Or for maximum adjustment, consider placing two swiveling elbow fittings together. Made of brass.

Description

Create a swiveling 90 degree elbow bend using any Koolance G 1/4 threaded nozzle. For a basic elbow fitting, the [Koolance Coupling Adapter](#) could also be used. Or for maximum adjustment, consider placing two swiveling elbow fittings together. Made of brass.

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

Specifications

General

| | |
|-------------------------------|---------------------------------|
| Weight | 0.08 lb (0.04 kg) |
| Fitting Thread | G 1/4 BSPP |
| Materials | Brass, EPDM |
| Max Pressure @ 25°C | 8kgf/cm ² (113.8psi) |
| Max Temp. Operating Tolerance | 100°C (212°F) |

Additional Information

| | |
|----------------|--------------|
| Brand | Koolance |
| SKU | NZL-LXG1-BK |
| Weight | 0.0500 |
| Special Order | No |
| Fitting Type | Connector |
| Fitting Angle | 90 Degree |
| Fitting Finish | Matte Black |
| Vendor SKU/EAN | 829596906028 |

