

Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA

Toll Free: 888-381-8222

www.performance-pcs.com sales@performance-pcs.com



Follow Us Twitter







Vandal Resistant Illuminated Momentary Switch - Black - 18/16mm

\$9.95


Product Images


















Short Description

The vandal resistant momentary on/off switch is the ideal switch for computer modding enthusiasts. A momentary switch is typically used for a PC's power and reset button. When turned on, the ring or dot around the push button illuminates in the specified color. Easy to install and will fit it many case switch holes, on a regular 3.5 or 5.25 inch bay cover, or wherever you chose to mount it.

Description

The vandal resistant momentary on/off switch is the ideal switch for computer modding enthusiasts. A momentary switch is typically used for a PC's power and reset button. When turned on, the ring or dot around the push button illuminates in the specified color. Easy to install and will fit it many case switch holes, on a regular 3.5 or 5.25 inch bay cover, or wherever you chose to mount it.

Manufactured from aluminum, this extensive range of vandal resistant security switches are designed for use in potentially hostile environments, such as access control applications, auto, truck, outdoor, marine use, or, in the case of PC modders, powering up your case to "on" or for use as a computer reset button.

This is a bare switch only and will need wiring to be able to use. Optional cable harness' can be ordered along with the switch. Wiring instructions are included.

Features

- Front Panel Mounting
- No LED Illumination
- 18mm Bezel diameter
- 16mm Shaft diameter
- S.P. Push to Make
- 50mA, 24V dc contact rating Switch

Specifications

• Terminations: (2.8mm tabs)

• Switching: S.P. Push to make, tactile S.P.

• Max. Rating: 50mA, 24V d.c. switch

• Contact Resistance: <100m Ω .

• Insulation Resistance: >103 M Ω .

• Dielectric Strength: Contact to Panel >2.0kV

• Contact to Contact 1500V Contact

• Operating Temp. Range: .30C to +70C

• Sealing (Front of panel only): Protection Classification: IP66 EN60529

• Materials:

Switch assembly: V-0 rated Polyamide (Nylon)

Tags: Copper Alloy Terminals: Copper Alloy

Switch Body & Button: Aluminum O rings: Nitrile and Silicone Contact Plate: Gold Plated

Additional Information

Brand	Mod/Smart
SKU	VSW18-MOM-BK
Weight	0.1500
Color	Black
Switch Type	Vandal (Momentary)
Material	Aluminum

4/10/24

