



Performance-PCs.com

1701 R. J. Conlan Blvd. NE, Unit #5 Palm Bay, FL 32905, USA



Like Us Facebook
Image: Control of the second s





www.performance-pcs.com sales@performance-pcs.com

Koolance QDC (High Flow) No-Spill Shutoff, Female Angle Barb [For ID: 13mm (1/2in)]

Special Price \$13.56 was \$16.95

Product Images



Description

Koolance (patent-pending) quick-disconnect no-spill shutoff valve. 13mm (1/2") ID female swiveling elbow connection with hose barb and clamp. It will only fit any Koolance VL3N male shutoff valve.

After a quarter twist, the quick-disconnect nozzles will separate. Liquid on both sides will be automatically obstructed with only

0.2mL freed. Nozzles are nickel-plated brass. Maximum operating pressure is 2-2.5kgf/cm2 (28-35 psi). Maximum operating temperature is 90°C.

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Features

NOTE: Liquid Coolants Koolance's product warranty does not cover the use of 3rd-party coolants, coolant additives, or corrosion. Koolance LIQ-702 or LIQ-705 coolants are strongly recommended to help avoid issues with mixed metals or biological growth. Additionally, do not use aluminum with bare (unplated) copper or bare (unplated) brass in the same system. Do not use silver with nickel in the same system.

Additional Information

Brand	Koolance
SKU	VL3N-F13LB-D
Weight	0.2000
Special Order	No
Fitting Type	Disconnect
Fitting Size	1/2"
Fitting Angle	90 Degree
Vendor SKU/EAN	829596905052
Special Price	\$13.56

